



Hood type dishwasher double skin heat recovery system 50x50 - 400 V		
Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher




- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: LCD multifunction display
- Number of programs: 13
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle [l/basket]: 2,2
- Washing cycle time [s/basket]: 60-90-180
- Detergent and rinse pump system: ProDose accurate dosing with a peristaltic pump
- Wash pump type: two-way DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: Evolution3 double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste

SAP Code	00011295	Boiler power [kW]	7.000
Net Width [mm]	836	Basin volume [l]	22
Net Depth [mm]	721	Tank power [kW]	2.500
Net Height [mm]	2265	Water consumption of the washing cycle [l/basket]	2,2
Net Weight [kg]	111.00	Washing cycle time [s/basket]	60-90-180
Power electric [kW]	10.200	Door clear height [mm]	465
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [ l ]	12.00		



Technical drawing

Hood type dishwasher double skin heat recovery system 50x50 - 400 V		
Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher







Hood type dishwasher double skin heat recovery system 50x50 - 400 V		
Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher

Stainless steel outer shell construction round construction with stainless steel, rounded edges,

Deep-drawn bathtub

Washing arms with a component, common for washing and rinsing

> upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

**LED Display** proScreen 4 local display + 2 LED strips

**Double pump** unique two-way DuoFlow pump

**Molded basket supports** guide rails for the baskets molded from the body of the dishwasher

**Detergent dispensers** two detergent and rinse aid dispensers

**Double filter system** the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

**Energy saving** energy saving energy saving system due to lowering the temperature of the boiler

**Protection of fragile dishes** softstart system for gradual start of washing programs to protect fragile dishes

#### **Double shell construction**

stainless steel construction with insulated double jacket

**Fast heating** performance management allows the current running of the boiler and basins body

**Possibility of recovery** saving up to 40% of boiler energy improves the comfort environment of the workplace environment without steam saves water

> e-mail: rmgastro@rmgastro.com web: www.rmgastro.com



### Technical parameters

Hood type dishwasher double s	kin heat recovery syste	em 50x50 - 400 V
Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher
<b>1. SAP Code:</b> 00011295		<b>15. Number of programs:</b> 13
2. Net Width [mm]: 836		<b>16. Opening of device:</b> Flip up
3. Net Depth [mm]: 721		17. Door clear height [mm]: 465
4. Net Height [mm]: 2265		18. Inlet pressure [bar]: 2-4
5. Net Weight [kg]: 111.00		19. Adjustable feet: Yes
6. Gross Width [mm]:		20. Number of skin:
7. Gross depth [mm]:		21. Self-cleaning cycle: Yes
8. Gross Height [mm]: 2314		22. Boiler capacity [ l ]: 12.00
9. Gross Weight [kg]: 121.00		23. Boiler power [kW]: 7.000
10. Device type: Electric unit		24. Basin volume [l]:
11. Control type: Digital		25. Tank power [kW]: 2.500
12. Material: Stainless steel		26. Number of arms for both rinsing and washing:
13. Power electric [kW]: 10.200		27. Arm connection: Hand loosen/tighten screw
14. Loading:		28. Washing arm type:

400 V / 3N - 50 Hz

Rotatable two-pronged



### Technical parameters

Hood type dishwasher double skin heat recovery system 50x50 - 400 V		
Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher
<b>29. Washing arm material:</b> Stainless steel		<b>39. Rack feed capacity:</b> 60-40-20
30. Atmospheric boiler with rinse pump: Yes		<b>40. Detergent and rinse pump system:</b> ProDose - accurate dosing with a peristaltic pump
31. Rinsing arm type: Rotating two-pronged		<b>41. Energy Saving system:</b> EnergySaving - Energy saving system due to lowering the boiler temperature
<b>32. Rinsing arm material:</b> Stainless steel		<b>42. Rinse system:</b> UltraRinse2 - stainless steel rinsing arms including stainless steel nozzles with a geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure
33. Deep drawn tank: Yes		43. Heating system:  HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle
34. Rack support: Pressed		<b>44. Quick heating system:</b> QuickReady - System for rapid heating of water in the tank
<b>35. Tank surface strainers:</b> stainless steel		<b>45. Lift system:</b> ProGlide - Required lifting force equals 3 kg thanks to counterweights and gentle guidance, reduces operator fatigue
<b>36. Drain filter:</b> Evolution3 - double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste		46. Heat recovery:  1 copper-aluminum battery - saving up to 40% of the energy needed to heat the water in the boiler, at the same time, by absorbing the released steam, it eliminates the need to use a hood

#### 38. Boiler thermostat adjust:

Yes

Yes

37. Thermostop:

#### 48. Closing door system:

Yes

47. Hot water electric valve:

ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes



### Technical parameters

Hood type dishwasher double skin heat recovery system 50x50 - 400 V		
Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher
<b>49. Rack size [mm]:</b> 500 × 500		<b>63. Program ProFessional:</b> Yes
<b>50. Display type:</b> LCD multifunction display		<b>64. Program ProTemp:</b> Yes
<b>51. Location of control panel:</b> On the top		65. Program ProClean: Yes
<b>52. USB port:</b> Yes, for Firmware actualisation		<b>66. Program ProDrain:</b> Yes
53. Drain pump: Yes		67. Program ProEco: Yes
<b>54. Self-diagnostics:</b> Yes		<b>68. Program ProNew:</b> Yes
<b>55. Wash pump type:</b> two-way - DuoFlow		<b>69. Program ProLong:</b> Yes
<b>56. Detergent dispenser:</b> Yes		<b>70. Program ProGlass:</b> Yes
<b>57. Rinse aid dispenser:</b> Yes		71. Program ProWater: Yes
<b>58.</b> Water consumption of the washing cycle [l/basket]: 2,2		72. Program ProActive: Yes
<b>59. Washing cycle time [s/basket]:</b> 60-90-180		73. Program ProSteel: Yes
<b>60. Rinse water temperature [°C]:</b> 80		<b>74. Program ProSan:</b> Yes
<b>61. Standard equipment for device:</b> 1x glass basket, 1x plate basket, 1x c	utlery basket	75. Cross-section of conductors CU [mm²]: 2,5
62. Program ProSpeed:		76. Water supply connection:

Yes

3/4"



### Technical parameters

Hood type dishwasher double skin heat recovery system 50x50 - 400 V		
Model	SAP Code	00011295
TT 112 REC ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher

#### 77. Diameter nominal:

DN 50