Technical data sheet





Convection oven STEAMBOX electric 10x GN 1/1 touch digital Automatic cleaning Direct steam 400 V

Model SAP Code 00011593

- Steam type: Injection
- Number of GN / EN: 10
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Digital
- Humidity control: MeteoSystem regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Supersteam two steam saturation modes
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: No
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011593	Loading	400 V / 3N - 50 Hz
Net Width [mm]	860	Steam type	Injection
Net Depth [mm]	795	Number of GN / EN	10
Net Height [mm]	1115	GN / EN size in device	GN 1/1
Net Weight [kg]	168.00	GN device depth	65
Power electric [kW]	15.700	Control type	Digital

Technical data sheet





Convection oven STEAMBOX electric 10x GN 1/1 touch digital Automatic cleaning Direct steam 400 V

Model **SAP Code** 00011593

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets
- **Digital display** simple multi-line backlit display of 99 programs with 9

cooking phases - help with cooking even for less skilled cooks, safe

- baking even in the absence of an operator; create your own recipes; easy to use
- Weather system patented device for measuring steam saturation in real time and in steam mode, the only one on the market
 - precise information for the operator about the steam saturation in the cooking area
- Steam tuner a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process
 - possibility of cooking different types of cuisine, from very moist steam for typical Czech dishes to lowsaturated steam for e.g. French cuisine
- Pass-through door the door is also built into the back of the combi oven. while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen
 - the chef can dispense the food through the convecto machine, the customer can see the preparation and maintenance of the food during dispensing
- **Adaptation for roasting chickens** the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat
 - grease does not drain into the sewer, does not destroy the machine's waste system

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

- allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously
- **Premix burner** the only burner with a turbo pre-mixing gas with air

on the market the structure of the burner to V which prevents

backfill and banging This design saves 30 % of gas compared to conventional burners

- faster heat-up faster more comfortable operation
- **Automatic washing** integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler
 - the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 1% hygienic quality

Self-supporting shower

drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed

- allows food in the food processor to be rinsed out if necessary to speed up cooling
- Six-speed fan, reversible with automatic calculation of direction change

in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed

e-mail: rmgastro@rmgastro.com 2025-04-25 web: www.rmgastro.com

Technical parameters





Convection oven STEAMBOX e	lectric 10x GN 1/1 tou	ch digital Automatic cleaning Direct steam 400 V
Model	SAP Code	00011593
1. SAP Code: 00011593		14. Exterior color of the device: Stainless steel
2. Net Width [mm]: 860		15. Adjustable feet: Yes
3. Net Depth [mm]: 795		16. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
4. Net Height [mm]: 1115		17. Stacking availability: Yes
5. Net Weight [kg]: 168.00		18. Control type: Digital
6. Gross Width [mm]: 955		19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)
7. Gross depth [mm]: 920		20. Steam type: Injection
8. Gross Height [mm]: 1240		21. Chimney for moisture extraction: Yes
9. Gross Weight [kg]: 178.00		22. Delta T heat preparation: Yes
10. Device type: Electric unit		23. Automatic preheating: Yes
11. Power electric [kW]: 15.700		24. Automatic cooling: Yes
12. Loading: 400 V / 3N - 50 Hz		25. Unified finishing of meals EasyService:
13. Material:		26. Night cooking:

No

AISI 304





	C 20X 011 2/2 touch u	gital Automatic cleaning Direct steam 400 V
Model	SAP Code	00011593
7. Washing system:		40. Distance between the layers [mm]:
27. Washing system: Closed - efficient use of water and washing chemicals by repeated pumping		70
28. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets		41. Smoke-dry function: No
29. Multi level cooking: No		42. Interior lighting: Yes
30. Advanced moisture adjustment: Supersteam - two steam saturation modes		43. Low temperature heat treatment: Yes
31. Slow cooking: from 50 °C		44. Number of fans:
32. Fan stop: Immediate when the door is opened		45. Number of fan speeds: 6
33. Lighting type: LED lighting in the doors, on both sides		46. Number of programs: 99
34. Cavity material and shape: AISI 304, with rounded corners for easy cleaning		47. USB port: Yes, for uploading recipes and updating firmware
35. Reversible fan: Yes		48. Door constitution: Vented safety double glass, removable for easy cleaning
36. Sustaince box: Yes		49. Number of preset programs: 40
37. Heating element material: Incoloy		50. Number of recipe steps: 9
38. Probe: Optional		51. Minimum device temperature [°C]: 50

39. Shower:

volitelná

300

52. Maximum device temperature [°C]:

Technical data sheet



Technical parameters

Convection oven STEAMBOX e	lectric 10x GN 1/1 tou	ch digital Automatic cleaning Direct steam 400 V	
Model	SAP Code	00011593	
 53. Device heating type: Combination of steam and hot air 54. HACCP: Yes 55. Number of GN / EN: 10 		58. Food regeneration: Yes	
		59. Cross-section of conductors CU [mm²]: 5 60. Diameter nominal: DN 50	
			56. GN / EN size in device: GN 1/1
57. GN device depth:			

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com