



STEAMBOX gas convection oven 20x GN 1/1 touch digital Automatic cleaning Direct steam

Model **SAP Code** 00011599

- Steam type: Injection

- Number of GN / EN: 20

- GN / EN size in device: GN 1/1

- GN device depth: 65

- Control type: Digital

- Humidity control: MeteoSystem regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Supersteam two steam saturation modes
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: No
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011599	Power gas [kW]	38.000
Net Width [mm]	1200	Type of gas	Natural Gas
Net Depth [mm]	910	Steam type	Injection
Net Height [mm]	1850	Number of GN / EN	20
Net Weight [kg]	300.00	GN / EN size in device	GN 1/1
Power electric [kW]	0.800	GN device depth	65
Loading	230 V / 1N - 50 Hz	Control type	Digital

Technical data sheet





STEAMBOX gas convection oven 20x GN 1/1 touch digital Automatic cleaning Direct steam

Model SAP Code 00011599

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets
- Digital display

simple multi-line backlit display of 99 programs with 9 cooking phases

- help with cooking even for less skilled cooks, safe baking even in the absence of an operator; create your own recipes; easy to use
- Weather system

 patented device for measuring s

Steam tuner

patented device for measuring steam saturation in real time and in steam mode, the only one on the market

- precise information for the operator about the steam saturation in the cooking area
- a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process
 - possibility of cooking different types of cuisine, from very moist steam for typical Czech dishes to lowsaturated steam for e.g. French cuisine
- Pass-through door
 the door is also built into the back of the combi oven,
 while full control is retained from the side of the cook

while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen

- the chef can dispense the food through the convecto machine, the customer can see the preparation and maintenance of the food during dispensing
- Adaptation for roasting chickens

the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat

 grease does not drain into the sewer, does not destroy the machine's waste system A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

- allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously
- Premix burner

the only burner with a turbo pre -mixing gas with air on the market

the structure of the burner to V which prevents backfill and banging

This design saves 30 % of gas compared to conventional burners

- faster heat-up faster more comfortable operation
- Automatic washing

integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler

- the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 1% hygienic quality
- Self -supporting shower

drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed

- allows food in the food processor to be rinsed out if necessary to speed up cooling
- Six-speed fan, reversible with automatic calculation of direction change

in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed

Technical data sheet



Technical parameters

		igital Automatic cleaning Direct steam	
Model	SAP Code	00011599	
1. SAP Code:		14. Type of gas:	
00011599		Natural Gas ————————————————————————————————————	
2. Net Width [mm]: 1200		15. Material: AISI 304	
3. Net Depth [mm]: 910		16. Exterior color of the device: Stainless steel	
4. Net Height [mm]: 1850		17. Adjustable feet: Yes	
5. Net Weight [kg]: 300.00		18. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)	
6. Gross Width [mm]: 1150		19. Stacking availability: No	
7. Gross depth [mm]: 1050		20. Control type: Digital	
8. Gross Height [mm]: 2100		21. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)	
9. Gross Weight [kg]: 310.00		22. Steam type: Injection	
LO. Device type: Gas unit		23. Chimney for moisture extraction: Yes	
11. Power electric [kW]: 0.800		24. Delta T heat preparation: Yes	
12. Loading: 230 V / 1N - 50 Hz		25. Automatic preheating: Yes	
13. Power gas [kW]:		26. Automatic cooling:	

Yes

38.000

Technical parameters





STEAMBOX gas convection oven 20x GN 1/1 touch digital	Automatic cleaning Direct steam	
Model SAP Code	00011599	
27. Unified finishing of meals EasyService:	40. Shower: Hand winder	
No	nand winder	
28. Night cooking: No	41. Distance between the layers [mm]: 70	
29. Washing system:	42. Smoke-dry function:	
Closed - efficient use of water and washing chemicals by repeated pumping	No	
30. Detergent type:	43. Interior lighting:	
Liquid washing detergent + liquid rinse aid/vinegar or washing tablets	Yes	
31. Multi level cooking:	44. Low temperature heat treatment:	
No	Yes	
32. Advanced moisture adjustment:	45. Number of fans:	
Supersteam - two steam saturation modes		
33. Slow cooking:	46. Number of fan speeds:	
from 50 °C	6	
34. Fan stop:	47. Number of programs:	
Immediate when the door is opened	99	
35. Lighting type:	48. USB port:	
LED lighting in the doors, on both sides	Yes, for uploading recipes and updating firmware	
36. Cavity material and shape:	49. Door constitution:	
AISI 304, with rounded corners for easy cleaning	Vented safety double glass, removable for easy cleaning	
37. Reversible fan: Yes	50. Number of preset programs: 40	
38. Sustaince box: Yes	51. Number of recipe steps: 9	

39. Probe:

Yes

52. Minimum device temperature [°C]:

Technical data sheet



Technical parameters

STEAMBOX gas convection ov	en 20x GN 1/1 touch di	gital Automatic cleaning Direct steam	
Model	SAP Code	00011599	
53. Maximum device temperature [°C]: 300		58. GN device depth: 65	
54. Device heating type: Combination of steam and ho	t air	59. Food regeneration: Yes	
55. HACCP: Yes		60. Connection to a ball valve: 1/2	
56. Number of GN / EN:		61. Diameter nominal:	
20		DN 50 	
57. GN / EN size in device:		62. Water supply connection:	

3/4"

GN 1/1