

# Technical data sheet



## Product features

### Conveyor toaster 2x holders with regulation

<b>Model</b>	<b>SAP Code</b>	00004519
TN 30 plus	<b>A group of articles - web</b>	Toasters



- Material: Stainless steel
- Indicators: operation and warm-up
- Removable rear wall of the device: Yes
- Width of internal part [mm]: 305
- Depth of internal part [mm]: 500
- Heating location: Upper and lower

<b>SAP Code</b>	00004519	<b>Net Weight [kg]</b>	22.00
<b>Net Width [mm]</b>	490	<b>Power electric [kW]</b>	3.200
<b>Net Depth [mm]</b>	540	<b>Loading</b>	230 V / 1N - 50 Hz
<b>Net Height [mm]</b>	400		

# Technical data sheet



## Product benefits

### Conveyor toaster 2x holders with regulation

Model	SAP Code	00004519
TN 30 plus	A group of articles - web	Toasters

**1 All-stainless design**  
only stainless steel intended for food contact is used

**2 Run and warm-up light**  
optical possibility to check the status of the device

**3 Separate control for individual sections**  
the possibility of a heating system separately

**4 Catch container for breadcrumbs**  
breadcrumbs fall outside the furnace

**5 Continuous toaster**  
automatic toast advance

**6 Continuous feed adjustment**  
possibility to change the speed of the sliding belt

**7 Silicon heaters**  
immediate onset of heat  
intense radiant heat

# Technical data sheet

## Technical parameters



### Conveyor toaster 2x holders with regulation

<b>Model</b>	<b>SAP Code</b>	00004519
TN 30 plus	<b>A group of articles - web</b>	Toasters

**1. SAP Code:**

00004519

**2. Net Width [mm]:**

490

**3. Net Depth [mm]:**

540

**4. Net Height [mm]:**

400

**5. Net Weight [kg]:**

22.00

**6. Gross Width [mm]:**

515

**7. Gross depth [mm]:**

750

**8. Gross Height [mm]:**

440

**9. Gross Weight [kg]:**

23.00

**10. Device type:**

Electric unit

**11. Construction type of device:**

Table top

**12. Material:**

Stainless steel

**13. Power electric [kW]:**

3,200

**14. Loading:**

230 V / 1N - 50 Hz

**15. Heating element material:**

Silicon tube

**16. Protection of controls:**

IPX4

**17. Toasting time:**

60 – 240

**18. Removable rear wall of the device:**

Yes

**19. Indicators:**

operation and warm-up

**20. Width of internal part [mm]:**

305

**21. Depth of internal part [mm]:**

500

**22. Heating location:**

Upper and lower

**23. Cross-section of conductors CU [mm<sup>2</sup>]:**

0,75