

Technical data sheet

Product features



Fry-top griddle plate 32x48 electric chromed smooth without cabinet 230 V

Model	SAP Code	00001151
FTHC 30 EL	A group of articles - web	Grills and grill plates



- Top type: Smooth
- Griddle dimensions [mm x mm]: 320 x 480
- Griddle thickness [mm]: 10.00
- Container for liquid fat: Yes
- Maximum device temperature [°C]: 300
- Removable rim: No

SAP Code	00001151	Power electric [kW]	3.000
Net Width [mm]	328	Loading	230 V / 1N - 50 Hz
Net Depth [mm]	609	Griddle dimensions [mm x mm]	320 x 480
Net Height [mm]	290	Top type	Smooth
Net Weight [kg]	23.00		

Technical data sheet



Product benefits

Fry-top griddle plate 32x48 electric chromed smooth without cabinet 230 V

Model	SAP Code	00001151
FTHC 30 EL	A group of articles - web	Grills and grill plates

1

All-stainless design

long life
resistance of AISI 304 stainless steel material
the material does not cut

2

Degree of protection of the control elements IPX4

maintenance-free system
resistance to splash water
long life

3

Outlet for waste liquids

ensures that oil drips into the socket

4

High non-removable hem

better hygienic conditions
preventing grease from splashing onto
ancillary equipment

5

Smooth plate made of chrome-plated steel

the product bakes less and is easier to clean
a good warming of the meat with a groove

6

Cooking unit for use on a table or on a base

variable use
the possibility of placement in smaller spaces

Technical data sheet

Technical parameters



Fry-top griddle plate 32x48 electric chromed smooth without cabinet 230 V

Model	SAP Code	00001151
FTHC 30 EL	A group of articles - web	Grills and grill plates

1. SAP Code:

00001151

2. Net Width [mm]:

328

3. Net Depth [mm]:

609

4. Net Height [mm]:

290

5. Net Weight [kg]:

23.00

6. Gross Width [mm]:

395

7. Gross depth [mm]:

705

8. Gross Height [mm]:

482

9. Gross Weight [kg]:

29.00

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Power electric [kW]:

3.000

13. Loading:

230 V / 1N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 430

16. Indicators:

operation and warm-up

17. Maximum device temperature [°C]:

300

18. Minimum device temperature [°C]:

50

19. Adjustable feet:

Yes

20. Griddle dimensions [mm x mm]:

320 x 480

21. Griddle thickness [mm]:

10.00

22. Container for liquid fat:

Yes

23. Removable rim:

No

24. Uniform heating:

Yes

25. Top type:

Smooth

26. Cross-section of conductors CU [mm²]:

0,75