

# Technical data sheet

## Product features



### Undercounter dishwasher single skin 50x50 - 230 V

| Model | SAP Code | 00011266 |
|-------|----------|----------|
|-------|----------|----------|



- Display type: 3 local display + diode bar
- Number of programs: 5
- Number of skin: 1
- Door clear height [mm]: 365
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle [l/basket]: 2,1
- Washing cycle time [s/basket]: 60-120-150
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

|                              |                    |                                                          |            |
|------------------------------|--------------------|----------------------------------------------------------|------------|
| <b>SAP Code</b>              | 00011266           | <b>Boiler power [kW]</b>                                 | 3.000      |
| <b>Net Width [mm]</b>        | 575                | <b>Basin volume [l]</b>                                  | 20         |
| <b>Net Depth [mm]</b>        | 605                | <b>Tank power [kW]</b>                                   | 2.000      |
| <b>Net Height [mm]</b>       | 820                | <b>Water consumption of the washing cycle [l/basket]</b> | 2,1        |
| <b>Net Weight [kg]</b>       | 54.00              | <b>Washing cycle time [s/basket]</b>                     | 60-120-150 |
| <b>Power electric [kW]</b>   | 3.500              | <b>Door clear height [mm]</b>                            | 365        |
| <b>Loading</b>               | 230 V / 1N - 50 Hz | <b>Rack size [mm]</b>                                    | 500 x 500  |
| <b>Boiler capacity [ l ]</b> | 6.00               | <b>Noise of device</b>                                   | 59,5       |

# Technical data sheet

Technical drawing





Undercounter dishwasher single skin 50x50 - 230 V

Model

SAP Code

00011266



# Technical data sheet



## Product benefits

### Undercounter dishwasher single skin 50x50 - 230 V

Model

SAP Code

00011266

1

#### **Stainless steel outer shell construction**

round construction with stainless steel, rounded edges, partially pressed tub

- easy cleaning, high hygiene standard, long service life

2

#### **Washing arms with a component, common for washing and rinsing**

washing arms made of composite material  
common arm for washing and rinsing  
integrated screw secured against falling out

- easy and safe handling during cleaning; higher user comfort

3

#### **LED Display**

three-line display  
diode strip

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

4

#### **Double pump**

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

5

#### **Molded basket supports**

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

6

#### **Detergent dispensers**

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

7

#### **Double filter system**

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

8

#### **Energy saving**

energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

# Technical data sheet

## Technical parameters



### Undercounter dishwasher single skin 50x50 - 230 V

**Model**

**SAP Code**

00011266

**1. SAP Code:**

00011266

**2. Net Width [mm]:**

575

**3. Net Depth [mm]:**

605

**4. Net Height [mm]:**

820

**5. Net Weight [kg]:**

54.00

**6. Gross Width [mm]:**

625

**7. Gross depth [mm]:**

655

**8. Gross Height [mm]:**

870

**9. Gross Weight [kg]:**

60.00

**10. Device type:**

Electric unit

**11. Control type:**

Digital

**12. Material:**

AISI 304

**13. Power electric [kW]:**

3.500

**14. Loading:**

230 V / 1N - 50 Hz

**15. Number of programs:**

5

**16. Opening of device:**

Tilting down

**17. Door clear height [mm]:**

365

**18. Inlet pressure [bar]:**

2-4

**19. Adjustable feet:**

Yes

**20. Number of skin:**

1

**21. Self-cleaning cycle:**

Yes

**22. Boiler capacity [ l ]:**

6.00

**23. Boiler power [kW]:**

3.000

**24. Basin volume [l]:**

20

**25. Tank power [kW]:**

2.000

**26. Number of arms for both rinsing and washing:**

2

**27. Arm connection:**

Hand loosen/tighten screw

**28. Washing arm type:**

Rotatable two-pronged

# Technical data sheet

## Technical parameters



### Undercounter dishwasher single skin 50x50 - 230 V

**Model**

**SAP Code**

00011266

**29. Washing arm material:**

Composite

**30. Rinsing arm type:**

Rotating two-pronged

**31. Rinsing arm material:**

Composite

**32. Rack support:**

Pressed

**33. Tank surface strainers:**

composite

**34. Drain filter:**

ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

**35. Thermostop:**

Yes

**36. Boiler thermostat adjust:**

Yes

**37. Rack feed capacity:**

24-30-60

**38. Detergent and rinse pump system:**

ProDose - accurate dosing with a peristaltic pump

**39. Energy Saving system:**

EnergySaving - Energy saving system due to lowering the boiler temperature

**40. Hot water electric valve:**

Yes

**41. Rack size [mm]:**

500 x 500

**42. Display type:**

3 local display + diode bar

**43. USB port:**

Yes, for Firmware actualisation

**44. Self-diagnostics:**

Yes

**45. Wash pump type:**

two-way - DuoFlow

**46. Detergent dispenser:**

Yes

**47. Rinse aid dispenser:**

Yes

**48. Water consumption of the washing cycle [l/basket]:**

2,1

**49. Washing cycle time [s/basket]:**

60-120-150

**50. Rinse water temperature [°C]:**

80

**51. Standard equipment for device:**

1x glass basket, 1x plate basket, 1x cutlery basket

**52. Program ProSpeed:**

Yes

**53. Program ProFessional:**

Yes

**54. Program ProTemp:**

Yes

# Technical data sheet

Technical parameters



Undercounter dishwasher single skin 50x50 - 230 V

Model

SAP Code

00011266

**55. Program ProSelf:**

Yes

**58. Cross-section of conductors CU [mm²]:**

1

**56. Program ProLong:**

Yes

**59. Water supply connection:**

3/4"

**57. Noise of device:**

59,5

**60. Diameter nominal:**

DN 50