

Combi convection steam oven electric 10x GN 1/1 automatic cleaning extra, direct steam 400 V		
Model	SAP Code	00011358
		 Steam type: Injection
		– Number of GN / EN: 10
		– GN / EN size in device: GN 1/1
		– GN device depth: 65
		 Control type: Touchscreen + buttons
		– Display size: 5"
		 Humidity control: Yes, indirect measuring
		 Advanced moisture adjustment: No
		 Delta T heat preparation: Yes
		 Multi level cooking: Drawer program - control of heat treatment for each dish separately
		 Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011358	Steam type	Injection
Net Width [mm]	870	Number of GN / EN	10
Net Depth [mm]	750	GN / EN size in device	GN 1/1
Net Height [mm]	1050	GN device depth	65
Net Weight [kg]	100.00	Control type	Touchscreen + buttons
Power electric [kW]	17.300	Display size	5"
Loading	400 V / 3N - 50 Hz		



Combi convection steam oven electric 10x GN 1/1 automatic cleaning extra, direct steam 400 V

Model

SAP Code

00011358



Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets

Touch screen display

simple intuitive control with unique pictograms, all in Czech

the possibility of using preset programs or manual control

- help with cooking even for less skilled cooks
- the possibility of safe cooking even in the absence of the operator
- creating your own recipes



A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

 allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously

Automatic washing

integrated chamber washing system the possibility of using liquid and tablet detergents option to use vinegar as a rinse aid the system also descales the micro boiler

 the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 100% hygienic quality

Six-speed reversible fan

ensures perfect distribution of steam without losing its saturation

its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed

6

External temperature probe

temperature probe located outside the cooking area, option of choosing one point or vacuum probe

 positioning outside the cooking chamber extends its life; ensuring total food hygiene safety; HACCP record; control of heat treatment in the absence of the cook

USB

downloading service reports upgrade software playing recipes

- quick fault finding
- transfer of original recipes
- keeping software up to date

Temperature range 3°C - 3°C

heating the chamber in the temperature range of 30 to 300 $^\circ\mathrm{C}$

- Possibility to prepare a large variety of dishes, from low-temperature baking to grilling, gratinating, etc.

Stainless steel construction

construction material is high quality stainless steel ensuring long life high hygiene standard

- safe food preparation; long service life; easy cleaning

Reinforced version

reinforced heating elements in the chamber higher power input

- Suitable for heavier workloads

10



Combi convection steam oven ele	ectric 10x GN 1/1 au	tomatic cleaning extra, direct steam 400 V
Model	SAP Code	00011358
1. SAP Code: 00011358		15. Adjustable feet: Yes
2. Net Width [mm]:		16. Humidity control:
870		Yes, indirect measuring
3. Net Depth [mm]:		17. Stacking availability:
750		Yes
4. Net Height [mm]: 1050		18. Control type: Touchscreen + buttons
5. Net Weight [kg]: 100.00		19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)
6. Gross Width [mm]:		20. Steam type:
940		Injection
7. Gross depth [mm]:		21. Sturdier version:
900		Yes
8. Gross Height [mm]:		22. Chimney for moisture extraction:
1160		Yes
9. Gross Weight [kg]:		23. Delayed start:
130.00		Yes
10. Device type:		24. Display size:
Electric unit		5"
11. Power electric [kW]:		25. Delta T heat preparation:
17.300		Yes
12. Loading: 400 V / 3N - 50 Hz		26. Unified finishing of meals EasyService:
13. Material:		27. Night cooking:
AISI 304		Yes
14. Exterior color of the device:		28. Washing system:
Stainless steel		Open

Technical parameters



Combi convection steam oven electric 10x GN 1/1 automatic cleaning extra, direct steam 400 V		
Model S.	AP Code	00011358
29. Detergent type: Liquid washing detergent + water rinse	2	43. Interior lighting: Yes
30. Multi level cooking: Drawer program - control of heat treatment for each dish separately		44. Low temperature heat treatment: Yes
31. Advanced moisture adjustment: No		45. Number of fans: 2
32. Slow cooking: from 50 °C		46. Number of fan speeds: 3
33. Fan stop: Interruption when door is opened, not braked		47. Number of programs: 1000
34. Lighting type: LED lighting in the door, on one side		48. USB port: Yes, for uploading recipes and updating firmware
5. Cavity material and shape: AISI 304, with rounded corners for easy	/ cleaning	49. Door constitution: Vented safety double glass, removable for easy cleaning
36. Reversible fan: Yes		50. Number of preset programs: 100
37. Sustaince box: Yes		51. Number of recipe steps: 9
8. Heating element material: Incoloy		52. Minimum device temperature [°C]: 50
9. Probe: Optional		53. Maximum device temperature [°C]: 300
0. Shower: Manual (optional)		54. Device heating type: Combination of steam and hot air
1. Distance between the layers [mm]: 74		55. HACCP: Yes
42. Smoke-dry function: Yes		56. Number of GN / EN: 10

4



Combi convection steam oven electric 10x GN 1/1 automatic cleaning extra, direct steam 400 V		
Model SAP	ode 00011358	
67. GN / EN size in device: GN 1/1	60. Cross-section of conductors CU [mm ²]: 5	
UN 1/1	 Výkon (kW): 37 a více (230 V); 64 a více (400 V) 	
8. GN device depth:	61. Diameter nominal:	
65	DN 50	
59. Food regeneration:	62. Water supply connection:	
Yes	3/4"	