

Technical data sheet

Product features



Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model	SAP Code	00011287
--------------	-----------------	----------



- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: ProScreen - 4 digit display + 2 LED bars
- Number of programs: 8
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle [l/basket]: 1,8
- Washing cycle time [s/basket]: 60-90-180
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

SAP Code	00011287	Boiler power [kW]	6.000
Net Width [mm]	600	Basin volume [l]	15
Net Depth [mm]	600	Tank power [kW]	1.400
Net Height [mm]	820	Water consumption of the washing cycle [l/basket]	1,8
Net Weight [kg]	55.00	Washing cycle time [s/basket]	60-90-180
Power electric [kW]	7.900	Door clear height [mm]	465
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [l]	6.00	Noise of device	59,3


Technical data sheet

Technical drawing



Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model	SAP Code	00011287
-------	----------	----------



Technical data sheet

Product benefits



Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model	SAP Code	00011287
-------	----------	----------

1 Stainless steel outer shell construction
round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life

2 Washing arms with a component, common for washing and rinsing
upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

- easy and safe handling during cleaning; higher user comfort

3 LED Display
proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

4 Double pump
unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

5 Molded basket supports
guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

6 Detergent dispensers
two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

7 Double filter system
the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

8 Energy saving
energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

9 Protection of fragile dishes
softstart system for gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

10 Double shell construction
stainless steel construction with insulated double jacket

- quiet operation
- energy saving

11 Fast heating
performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

Technical data sheet

Technical parameters



Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model	SAP Code	00011287
-------	----------	----------

1. SAP Code:

00011287

2. Net Width [mm]:

600

3. Net Depth [mm]:

600

4. Net Height [mm]:

820

5. Net Weight [kg]:

55.00

6. Gross Width [mm]:

650

7. Gross depth [mm]:

650

8. Gross Height [mm]:

870

9. Gross Weight [kg]:

63.00

10. Device type:

Electric unit

11. Control type:

Digital

12. Material:

Stainless steel

13. Power electric [kW]:

7.900

14. Loading:

400 V / 3N - 50 Hz

15. Number of programs:

8

16. Opening of device:

Tilting down

17. Door clear height [mm]:

465

18. Inlet pressure [bar]:

2-4

19. Adjustable feet:

Yes

20. Number of skin:

2

21. Self-cleaning cycle:

Yes

22. Boiler capacity [l]:

6.00

23. Boiler power [kW]:

6.000

24. Basin volume [l]:

15

25. Tank power [kW]:

1.400

26. Number of arms for both rinsing and washing:

2

27. Arm connection:

Click-clack - easy removal with one hand

28. Washing arm type:

Rotatable two-pronged

Technical data sheet

Technical parameters



Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model	SAP Code	00011287
--------------	-----------------	----------

29. Washing arm material:

Composite

30. Rinsing arm type:

Rotating two-pronged

31. Rinsing arm material:

Composite

32. Deep drawn tank:

Yes

33. Rack support:

Pressed

34. Tank surface strainers:

composite

35. Drain filter:

ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

36. Thermostop:

Yes

37. Boiler thermostat adjust:

Yes

38. Rack feed capacity:

60-40-20

39. Detergent and rinse pump system:

ProDose - accurate dosing with a peristaltic pump

40. Energy Saving system:

EnergySaving - Energy saving system due to lowering the boiler temperature

41. Heating system:

HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

42. Hot water electric valve:

Yes

43. Closing door system:

ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes

44. Rack size [mm]:

500 x 500

45. Display type:

ProScreen - 4 digit display + 2 LED bars

46. USB port:

Yes, for Firmware actualisation

47. Drain pump:

Yes

48. Self-diagnostics:

Yes

49. Wash pump type:

two-way - DuoFlow

50. Detergent dispenser:

Yes

51. Rinse aid dispenser:

Yes

52. Water consumption of the washing cycle [l/basket]:

1,8

Technical data sheet

Technical parameters



Undercounter dishwasher double skin with drain pump 50x50 - 400 V

Model	SAP Code	00011287
--------------	-----------------	----------

53. Washing cycle time [s/basket]:

60-90-180

54. Rinse water temperature [°C]:

80

55. Standard equipment for device:

1x glass basket, 1x plate basket, 1x cutlery basket

56. Program ProSpeed:

Yes

57. Program ProFessional:

Yes

58. Program ProTemp:

Yes

59. Program ProClean:

Yes

60. Program ProDrain:

Yes

61. Program ProEco:

Yes

62. Program ProLong:

Yes

63. Program ProGlass:

Yes

64. Noise of device:

59,3

65. Cross-section of conductors CU [mm²]:

1,5

- Výkon (kW): 5-5,7 (230 V); 8,7-9,8 (400 V)

66. Water supply connection:

3/4"

67. Diameter nominal:

DN 50