

Technical data sheet



Product features

Fry-top griddle plate 31x65 electric grooved on open cabinet 400 V

Model	SAP Code	00012399
--------------	-----------------	----------



- Top type: Grooved
- Worktop material: Sandblasted steel
- Maximum device temperature [°C]: 300

SAP Code	00012399	Net Weight [kg]	71.00
Net Width [mm]	400	Power electric [kW]	6.000
Net Depth [mm]	900	Loading	400 V / 3N - 50 Hz
Net Height [mm]	900	Top type	Grooved

Technical data sheet



Product benefits

Fry-top griddle plate 31x65 electric grooved on open cabinet 400 V

Model

SAP Code

00012399

1

All-stainless design

- long life
- corrosion resistance of the top plate material
 - savings on service interventions
 - easier and faster operation

2

Degree of protection of the control elements IPX4

- maintenance-free system
- resistance to splash water
- long life
 - savings on service interventions
 - easy cleaning and maintenance of equipment

3

Outlet for waste liquids

- ensures that oil drips into the socket
 - easy maintenance
 - easy cleaning

4

High detachable hem

- better hygienic conditions
- preventing grease from splashing onto ancillary equipment
 - easy maintenance
 - easy cleaning

5

Ribbed steel plate

- fast heat transfer and the surface will not be scratched
- a good warming of the meat with a groove
 - time-saving in food preparation
 - easy preparation of good-looking food

Technical data sheet



Technical parameters

Fry-top griddle plate 31x65 electric grooved on open cabinet 400 V

Model	SAP Code	00012399
--------------	-----------------	----------

1. SAP Code:

00012399

12. Power electric [kW]:

6.000

2. Net Width [mm]:

400

13. Loading:

400 V / 3N - 50 Hz

3. Net Depth [mm]:

900

14. Protection of controls:

IPX4

4. Net Height [mm]:

900

15. Material:

AISI 304 top plate, AISI 430 cladding

5. Net Weight [kg]:

71.00

16. Worktop material:

Sandblasted steel

6. Gross Width [mm]:

970

17. Worktop Thickness [mm]:

15.00

7. Gross depth [mm]:

440

18. Maximum device temperature [°C]:

300

8. Gross Height [mm]:

1140

19. Minimum device temperature [°C]:

50

9. Gross Weight [kg]:

80.00

20. Adjustable feet:

Yes

10. Device type:

Electric unit

21. Top type:

Grooved

11. Construction type of device:

Stationary

22. Cross-section of conductors CU [mm²]:

1

- Výkon (kW): 3,7-5 (230 V); 6,4-8,7 (400 V)