



Undercounter dishwasher double skin 50x50 - 400 V		
Model	SAP Code	00011273
TT 52 T ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher




- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: LCD multifunction display
- Number of programs: 13
- Number of skin: 2
- Door clear height [mm]: 385
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle [l/basket]: 2,2
- Washing cycle time [s/basket]: 90-120-150
- Detergent and rinse pump system: ProDose accurate dosing with a peristaltic pump
- Wash pump type: two-way DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: Evolution3 double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste

SAP Code	00011273	Boiler power [kW]	6.000
Net Width [mm]	600	Basin volume [l]	15
Net Depth [mm]	600	Tank power [kW]	1.400
Net Height [mm]	820	Water consumption of the washing cycle [l/basket]	2,2
Net Weight [kg]	55.00	Washing cycle time [s/basket]	90-120-150
Power electric [kW]	7.900	Door clear height [mm]	385
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [l]	6.00		



Technical drawing

Undercounter dishwasher double skin 50x50 - 400 V		
Model	SAP Code	00011273
TT 52 T ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher







Undercounter dishwasher double skin 50x50 - 400 V		
Model	SAP Code	00011273
TT 52 T ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher

Stainless steel outer shell construction round construction with stainless steel, rounded edges,

round construction with stainless steel, rounded edges. Deep-drawn bathtub

2 Stainless steel washing arms upper and lower stainless steel swivel arms common

3 LED Display proScreen 4 local display + 2 LED strips

Two-way pump
unique two-way DuoFlow pump

Molded basket supports
guide rails for the baskets molded from the body of the dishwasher

Detergent dispensers
two detergent and rinse aid dispensers

7 Double filter system
the chamber filter and the waste filter together with the
ArchiMedes system provide a discharge system with
increased water purification efficiency

Fast heating

Performance management allows the current running of the boiler and basins body

Protection of fragile dishes
softstart system for gradual start of washing programs to protect fragile dishes

Double shell construction

stainless steel construction with insulated double jacket

Energy saving energy saving system due to lowering the temperature of the boiler

Fast heatingperformance management allows the current running of the boiler and basins body



Technical parameters

Undercounter dishwasher double	e skin 50x50 - 400 V	
Model	SAP Code	00011273
TT 52 T ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher
1. SAP Code: 00011273		15. Number of programs: 13
2. Net Width [mm]: 600		16. Opening of device: Tilting down
3. Net Depth [mm]: 600		17. Door clear height [mm]: 385
4. Net Height [mm]: 820		18. Adjustable feet: Yes
5. Net Weight [kg]: 55.00		19. Number of skin:
6. Gross Width [mm]: 650		20. Self-cleaning cycle: Yes
7. Gross depth [mm]: 650		21. Boiler capacity [l]: 6.00
8. Gross Height [mm]: 870		22. Boiler power [kW]: 6.000
9. Gross Weight [kg]: 63.00		23. Basin volume [l]:
10. Device type: Electric unit		24. Tank power [kW]: 1.400
11. Control type: Digital		25. Number of arms for both rinsing and washing:
12. Material: Stainless steel		26. Arm connection: Hand loosen/tighten screw
13. Power electric [kW]: 7.900		27. Washing arm type: Rotatable two-pronged

14. Loading:

400 V / 3N - 50 Hz

28. Washing arm material:

Stainless steel



Technical parameters

U	ndercounter dishwasher double	skin 50x50 - 400 V	
M	lodel	SAP Code	00011273
Т	T 52 T ABT	A group of articles - web	Undercounter, continuous and black ware dishwasher
29.	Atmospheric boiler with rinse p Yes	ump:	40. Energy Saving system: EnergySaving - Energy saving system due to lowering the boiler temperature
30. Rinsing arm type: Rotating two-pronged			41. Rinse system: ProRinse - composite arms common for rinsing and washing with geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure
31.	31. Rinsing arm material: Stainless steel		42. Heating system: HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle
32.	32. Deep drawn tank: Yes		43. Quick heating system: QuickReady - System for rapid heating of water in the tank
33.	33. Rack support: Pressed		44. Hot water electric valve: Yes
34.	34. Tank surface strainers: stainless steel		45. Closing door system: ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes
35.	35. Drain filter: Evolution3 - double filtration with electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water to waste		46. Rack size [mm]: 500 x 500
36.	36. Thermostop: Yes		47. Display type: LCD multifunction display
37.	37. Boiler thermostat adjust: Yes		48. USB port: Yes, for Firmware actualisation
38.	38. Rack feed capacity: 60-40-20		49. Drain pump: Yes

39. Detergent and rinse pump system:

ProDose - accurate dosing with a peristaltic pump

50. Self-diagnostics:



Technical parameters

Undercounter dishwasher double skin 50x50 - 400 V		
Model SAP Code	00011273	
TT 52 T ABT A group of articles - web	Undercounter, continuous and black ware dishwasher	
51. Wash pump type: two-way - DuoFlow	63. Program ProEco: Yes	
52. Detergent dispenser: Yes	64. Program ProNew: Yes	
53. Rinse aid dispenser: Yes	65. Program ProLong: Yes	
54. Water consumption of the washing cycle [l/basket]: 2,2	66. Program ProGlass: Yes	
55. Washing cycle time [s/basket]: 90-120-150	67. Program ProWater: Yes	
56. Rinse water temperature [°C]: 80	68. Program ProActive: Yes	
57. Standard equipment for device: 1x glass basket, 1x plate basket, 1x cutlery basket	69. Program ProSteel: Yes	
58. Program ProSpeed: Yes	70. Program ProSan: Yes	
59. Program ProFessional: Yes	71. Cross-section of conductors CU [mm²]:	
60. Program ProTemp: Yes	72. Water supply connection: 3/4"	
61. Program ProClean: Yes	73. Diameter nominal: DN 50	

62. Program ProDrain:

Yes