

# Technical data sheet

## Product features



### Sausage roaster 10 rolls

|              |                                  |                 |
|--------------|----------------------------------|-----------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00019406        |
| CW 10/44     | <b>A group of articles - web</b> | Sausage warmers |



- Material: Stainless steel
- Indicators: operation and warm-up
- Minimum device temperature [°C]: 80
- Maximum device temperature [°C]: 300
- Number of internal parts: 9
- Tubes length [mm]: 440

|                        |          |                                        |                    |
|------------------------|----------|----------------------------------------|--------------------|
| <b>SAP Code</b>        | 00019406 | <b>Power electric [kW]</b>             | 2.250              |
| <b>Net Width [mm]</b>  | 540      | <b>Loading</b>                         | 230 V / 1N - 50 Hz |
| <b>Net Depth [mm]</b>  | 430      | <b>Number of internal parts</b>        | 9                  |
| <b>Net Height [mm]</b> | 200      | <b>Minimum device temperature [°C]</b> | 80                 |
| <b>Net Weight [kg]</b> | 14.00    | <b>Maximum device temperature [°C]</b> | 300                |

# Technical data sheet

## Technical parameters



### Sausage roaster 10 rolls

|              |                                  |                 |
|--------------|----------------------------------|-----------------|
| <b>Model</b> | <b>SAP Code</b>                  | 00019406        |
| CW 10/44     | <b>A group of articles - web</b> | Sausage warmers |

**1. SAP Code:**

00019406

**2. Net Width [mm]:**

540

**3. Net Depth [mm]:**

430

**4. Net Height [mm]:**

200

**5. Net Weight [kg]:**

14.00

**6. Gross Width [mm]:**

600

**7. Gross depth [mm]:**

500

**8. Gross Height [mm]:**

230

**9. Gross Weight [kg]:**

15.00

**10. Device type:**

Electric unit

**11. Construction type of device:**

Table top

**12. Material:**

Stainless steel

**13. Power electric [kW]:**

2.250

**14. Loading:**

230 V / 1N - 50 Hz

**15. Minimum device temperature [°C]:**

80

**16. Maximum device temperature [°C]:**

300

**17. Protection of controls:**

IPX4

**18. Number of internal parts:**

9

**19. Tubes length [mm]:**

440

**20. Number of revolutions / min:**

0

**21. Indicators:**

operation and warm-up

**22. Cross-section of conductors CU [mm²]:**

0,5