

Technical data sheet

Product features



Conveyor toaster 2x holders

Model	SAP Code	00004520
TN 30	A group of articles - web	Toasters



- Material: Stainless steel
- Indicators: operation and warm-up
- Removable rear wall of the device: Yes
- Width of internal part [mm]: 305
- Depth of internal part [mm]: 500
- Heating location: Upper and lower

SAP Code	00004520	Net Weight [kg]	21.00
Net Width [mm]	490	Power electric [kW]	3.200
Net Depth [mm]	540	Loading	230 V / 1N - 50 Hz
Net Height [mm]	400		

Technical data sheet

Product benefits



Conveyor toaster 2x holders

Model	SAP Code	00004520
TN 30	A group of articles - web	Toasters

1

All-stainless design

only stainless steel intended for food contact is used

2

Run and warm-up light

optical possibility to check the status of the device

3

Separate control for individual sections

the possibility of a heating system separately

4

Catch container for breadcrumbs

breadcrumbs fall outside the furnace

5

Removable back wall

delete all

- possibility to open the back wall of the device

6

Continuous toaster

automatic toast advance

7

Silicon heaters

immediate onset of heat
intense radiant heat

Technical data sheet



Technical parameters

Conveyor toaster 2x holders

Model	SAP Code	00004520
TN 30	A group of articles - web	Toasters

1. SAP Code:

00004520

2. Net Width [mm]:

490

3. Net Depth [mm]:

540

4. Net Height [mm]:

400

5. Net Weight [kg]:

21.00

6. Gross Width [mm]:

515

7. Gross depth [mm]:

750

8. Gross Height [mm]:

440

9. Gross Weight [kg]:

22.00

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Material:

Stainless steel

13. Power electric [kW]:

3,200

14. Loading:

230 V / 1N - 50 Hz

15. Heating element material:

Silicon tube

16. Protection of controls:

IPX4

17. Toasting time:

100

18. Removable rear wall of the device:

Yes

19. Indicators:

operation and warm-up

20. Width of internal part [mm]:

305

21. Depth of internal part [mm]:

500

22. Heating location:

Upper and lower

23. Cross-section of conductors CU [mm²]:

0,75