

Product features

Combi convection steam oven electric 10x GN 1/1 automatic cleaning direct steam 400 V		
Model	SAP Code	00011356
EPD 1011 EAM	A group of articles - web	Convection machines

- Steam type: InjectionNumber of GN / EN: 10GN / EN size in device: GN 1/1
- GN device depth: 65
- Control tunos Touch
- Control type: Touchscreen + buttons
- Display size: 5"
- Humidity control: Yes, indirect measuring
- Advanced moisture adjustment: No
- Delta T heat preparation: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011356	Steam type	Injection
Net Width [mm]	870	Number of GN / EN	10
Net Depth [mm]	750	GN / EN size in device	GN 1/1
Net Height [mm]	1050	GN device depth	65
Net Weight [kg]	100.00	Control type	Touchscreen + buttons
Power electric [kW]	12.600	Display size	5"
Loading	400 V / 3N - 50 Hz		



Product benefits

Combi convection steam oven electric 10x GN 1/1 automatic cleaning direct steam 400 V			
Model	SAP Code	00011356	
EPD 1011 EAM	A group of articles - web	Convection machines	

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

Touch screen display

simple intuitive control with unique pictograms, all in Czech

the possibility of using preset programs or manual control

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other connects the connections, inlets, wastes and ventilation

connects the connections, inlets, wastes and ventilation of the lower combi oven

_ Automatic washing

integrated chamber washing system the possibility of using liquid and tablet detergents option to use vinegar as a rinse aid

the system also descales the micro boiler

Six-speed reversible fan

ensures perfect distribution of steam without losing its saturation

its operation is controlled by the program or manually

External temperature probe

temperature probe located outside the cooking area, option of choosing one point or vacuum probe

USBdownloading service reports

upgrade software playing recipes

Temperature range 3°C - 3°C

heating the chamber in the temperature range of 30 to 300 $^{\circ}\text{C}$

Stainless steel construction

construction material is high quality stainless steel ensuring long life high hygiene standard



Technical parameters

Model	SAP Code	00011356			
EPD 1011 EAM	A group of articles - web	Convection machines			
1. SAP Code: 00011356		15. Adjustable feet: Yes			
2. Net Width [mm]: 870		16. Humidity control: Yes, indirect measuring			
3. Net Depth [mm]: 750		17. Stacking availability: Yes			
4. Net Height [mm]: 1050 5. Net Weight [kg]: 100.00 6. Gross Width [mm]: 940		 18. Control type: Touchscreen + buttons 19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering) 20. Steam type: Injection 			
			7. Gross depth [mm]: 900		21. Sturdier version: No
			8. Gross Height [mm]: 1160		22. Chimney for moisture extraction: Yes
9. Gross Weight [kg]: 130.00		23. Delayed start: Yes			
LO. Device type: Electric unit		24. Display size: 5"			
L1. Power electric [kW]: 12.600		25. Delta T heat preparation: Yes			
L2. Loading: 400 V / 3N - 50 Hz		26. Unified finishing of meals EasyService: Yes			
L3. Material: AISI 304		27. Night cooking: Yes			
14. Exterior color of the device:		28. Washing system:			

Open

Stainless steel



Technical parameters

Combi convection steem even	olostvis 10v CN 1/1 auto	omatic cleaning direct steam 400 V
Model	SAP Code	00011356
EPD 1011 EAM	A group of articles - web	Convection machines
29. Detergent type: Liquid washing detergent + wate	er rinse	43. Interior lighting: Yes
B0. Multi level cooking: Drawer program - control of heat treatment for each dish separately B1. Advanced moisture adjustment: No		44. Low temperature heat treatment: Yes 45. Number of fans:
33. Fan stop: Interruption when door is open	ed, not braked	47. Number of programs: 1000
34. Lighting type: LED lighting in the door, on one side		48. USB port: Yes, for uploading recipes and updating firmware
85. Cavity material and shape: AISI 304, with rounded corners f	or easy cleaning	49. Door constitution: Vented safety double glass, removable for easy cleaning
86. Reversible fan: Yes		50. Number of preset programs: 100
87. Sustaince box: Yes		51. Number of recipe steps: 9
8. Heating element material: Incoloy		52. Minimum device temperature [°C]:
9. Probe: Optional		53. Maximum device temperature [°C]: 300
0. Shower: Manual (optional)		54. Device heating type: Combination of steam and hot air
11. Distance between the layers [mm]:		55. HACCP: Yes
42. Smoke-dry function:		56. Number of GN / EN:

Yes

10



Technical parameters

Combi convection steam oven e	lectric 10x GN 1/1 autom	atic cleaning direct steam 400 V	
Model	SAP Code	00011356	
EPD 1011 EAM	A group of articles - web	Convection machines	
57. GN / EN size in device: GN 1/1		60. Cross-section of conductors CU [mm ²]:	
58. GN device depth: 65		61. Diameter nominal: DN 50	_
59. Food regeneration:		62. Water supply connection:	

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com