

Technical data sheet

Product features



Regeneration oven REGBOX programmable 10x GN 1/1 - 400 V

Model	SAP Code	00010675
RD 1011 EP	A group of articles - web	RegBoxes



- Number of programs: 10
- Food regeneration: Yes
- Humidification: Yes
- Automatic preheating: Yes
- Maximum device temperature [°C]: 170
- Control type: Digital
- Probe: Injectable
- Number of GN / EN: 10
- GN / EN size in device: GN 1/1
- GN device depth: 150

SAP Code	00010675	Loading	400 V / 3N - 50 Hz
Net Width [mm]	820	Number of GN / EN	10
Net Depth [mm]	750	GN / EN size in device	GN 1/1
Net Height [mm]	1110	GN device depth	150
Net Weight [kg]	113.00	Control type	Digital
Power electric [kW]	12.600		

Technical drawing



Technical drawing of the EKO 1530 refrigerator, showing three views: front, top, and side.

Front View:

- Width: 1108 mm
- Height: 820 mm
- Top panel height: 60 mm
- Door handle height: 700 mm
- Bottom panel height: 60 mm
- Door type: Right-hand door (indicated by the symbol $\rightarrow$)

Top View:

- Width: 1530 mm
- Depth: 777 mm
- Top panel width: 284 mm
- Top panel depth: 199 mm
- Top panel height: 41 mm
- Top panel width (excluding top panel): 126 mm
- Top panel depth (excluding top panel): 521 mm
- Top panel width (excluding top panel and top panel): 99 mm
- Top panel depth (excluding top panel and top panel): 50 mm
- Top panel width (excluding top panel and top panel): 50 mm
- Top panel depth (excluding top panel and top panel): 99 mm

Side View:

- Height: 748 mm
- Depth: 521 mm
- Top panel height: 56 mm
- Top panel depth: 56 mm
- Top panel width: 56 mm
- Top panel depth (excluding top panel): 22 mm
- Top panel width (excluding top panel): 56 mm
- Top panel depth (excluding top panel and top panel): 56 mm
- Top panel width (excluding top panel and top panel): 56 mm
- Top panel depth (excluding top panel and top panel): 56 mm

Technical data sheet

Product benefits



Regeneration oven REGBOX programmable 10x GN 1/1 - 400 V

Model	SAP Code	00010675
RD 1011 EP	A group of articles - web	RegBoxes

1

All-stainless steel construction

round construction with stainless steel, rounded edges

2

External temperature probe

temperature probe located outside the cooking space

3

Programmable control

control allowing to set 10 programs

4

Temperature up to 170°C

powerful heating element made of Incoly material
temperature range from 30 to 170 °C

5

High mobility

the version with wheels and water pump can be used as a mobile device

Technical data sheet

Technical parameters



Regeneration oven REGBOX programmable 10x GN 1/1 - 400 V

Model	SAP Code	00010675
RD 1011 EP	A group of articles - web	RegBoxes

1. SAP Code:

00010675

2. Net Width [mm]:

820

3. Net Depth [mm]:

750

4. Net Height [mm]:

1110

5. Net Weight [kg]:

113.00

6. Gross Width [mm]:

940

7. Gross depth [mm]:

900

8. Gross Height [mm]:

1200

9. Gross Weight [kg]:

128.00

10. Device type:

Electric unit

11. Power electric [kW]:

12.600

12. Loading:

400 V / 3N - 50 Hz

13. Material:

AISI 304

14. Adjustable feet:

Yes

15. Control type:

Digital

16. Automatic preheating:

Yes

17. Number of GN / EN:

10

18. GN / EN size in device:

GN 1/1

19. GN device depth:

150

20. Maximum device temperature [°C]:

170

21. Humidification:

Yes

22. Probe:

Injectable

23. Number of programs:

10

24. Food regeneration:

Yes

25. Cross-section of conductors CU [mm²]:

4