Technical data sheet



Product features

Fry-top griddle plate 65x48 electric combined without cabinet 400 V

Model SAP Code 00001155



- Top type: Combinated
- Griddle dimensions [mm x mm]: 650 x 480
- Griddle thickness [mm]: 10.00
- Container for liquid fat: Yes
- Independent heating zones: Separate control for each heating zone
- Maximum device temperature [°C]: 300
- Surface finish: sandblasted surface without coating
- Removable rim: No

SAP Code	00001155	Power electric [kW]	6.000
Net Width [mm]	658	Loading	400 V / 3N - 50 Hz
Net Depth [mm]	609	Griddle dimensions [mm x mm]	650 x 480
Net Height [mm]	290	Top type	Combinated
Net Weight [kg]	45.00		

Technical data sheet



Product benefits

Fry-top griddle plate 65x48 electric combined without cabinet 400 V

Model **SAP Code** 00001155

All-stainless design

long life resistance of AISI 304 stainless steel material the material does not cut

- savings on service interventions
- easy cleaning and maintenance of equipment

Degree of protection of the control elements IPX4

maintenance-free system resistance to splash water long life

- savings on service interventions
- easy cleaning and maintenance of equipment

Outlet for waste liquids

ensures that oil drips into the socket

- easy maintenance
- easy cleaning

High non-removable hem

better hygienic conditions preventing grease from splashing onto ancillary equipment

- easy maintenance
- easy cleaning

Combined steel plate

good heat transfer and the surface does not get scratched enables preparation on smooth or grooved plates

- time-saving in food preparation
- easy preparation of different types of dishes

Cooking unit for use on a table or on a base

the possibility of placement in smaller spaces

- easy handling
- cost savings on substructure

e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

Technical data sheet



Technical parameters

Fry-top griddle plate 65x48 electric combined without cabinet 400 V			
Model	SAP Code	00001155	
1. SAP Code: 00001155		15. Material: AISI 430	
2. Net Width [mm]: 658		16. Indicators: operation and warm-up	
3. Net Depth [mm]: 609		17. Surface finish: sandblasted surface without coating	
4. Net Height [mm]: 290		18. Maximum device temperature [°C]: 300	
5. Net Weight [kg]: 45.00		19. Minimum device temperature [°C]: 50	
6. Gross Width [mm]: 725		20. Adjustable feet: Yes	
7. Gross depth [mm]: 710		21. Griddle dimensions [mm x mm]: 650 x 480	
8. Gross Height [mm]: 540		22. Griddle thickness [mm]: 10.00	
9. Gross Weight [kg]: 50.00		23. Container for liquid fat: Yes	
10. Device type: Electric unit		24. Independent heating zones: Separate control for each heating zone	
11. Construction type of device: Table top		25. Removable rim:	
12. Power electric [kW]: 6.000		26. Uniform heating: Yes	
13. Loading: 400 V / 3N - 50 Hz		27. Top type: Combinated	

28. Cross-section of conductors CU [mm²]:

IPX4

14. Protection of controls: