

Technical data sheet

Product features



Hood type dishwasher single skin controls on TOP 50x50 - 400 V

Model	SAP Code	00011315
QQI 102/TOP	A group of articles - web	Undercounter, continuous and black ware dishwasher



- Display type: 3 local display + diode bar
- Number of programs: 5
- Number of skin: 1
- Door clear height [mm]: 450
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle [l/basket]: 2,1
- Washing cycle time [s/basket]: 60-120-150
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

SAP Code	00011315	Boiler power [kW]	8.000
Net Width [mm]	634	Basin volume [l]	15
Net Depth [mm]	744	Tank power [kW]	2.100
Net Height [mm]	1530	Water consumption of the washing cycle [l/basket]	2,1
Net Weight [kg]	110.00	Washing cycle time [s/basket]	60-120-150
Power electric [kW]	8.500	Door clear height [mm]	450
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [l]	6.00	Noise of device	60,4

The Red Fox logo, featuring the words "RED FOX" in a bold, sans-serif font. "RED" is in red and "FOX" is in black, with a registered trademark symbol (®) to the upper right of "FOX". The logo is enclosed in a white rounded rectangle with a black border.

Technical data sheet



Product benefits

Hood type dishwasher single skin controls on TOP 50x50 - 400 V

Model	SAP Code	00011315
QQI 102/TOP	A group of articles - web	Undercounter, continuous and black ware dishwasher

1

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, partially pressed tub

2

Washing arms with a component, common for washing and rinsing

washing arms made of composite material
common arm for washing and rinsing
integrated screw secured against falling out

3

LED Display

three-line display
diode strip

4

Double pump

unique two-way DuoFlow pump

5

Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

6

Detergent dispensers

two detergent and rinse aid dispensers

7

Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

8

Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

Technical data sheet

Technical parameters



Hood type dishwasher single skin controls on TOP 50x50 - 400 V

Model	SAP Code	00011315
QQI 102/TOP	A group of articles - web	Undercounter, continuous and black ware dishwasher

1. SAP Code:

00011315

2. Net Width [mm]:

634

3. Net Depth [mm]:

744

4. Net Height [mm]:

1530

5. Net Weight [kg]:

110.00

6. Gross Width [mm]:

724

7. Gross depth [mm]:

818

8. Gross Height [mm]:

1579

9. Gross Weight [kg]:

120.00

10. Device type:

Electric unit

11. Control type:

Digital

12. Material:

AISI 304

13. Power electric [kW]:

8.500

14. Loading:

400 V / 3N - 50 Hz

15. Number of programs:

5

16. Opening of device:

Flip up

17. Door clear height [mm]:

450

18. Inlet pressure [bar]:

2-4

19. Adjustable feet:

Yes

20. Number of skin:

1

21. Self-cleaning cycle:

Yes

22. Boiler capacity [l]:

6.00

23. Boiler power [kW]:

8.000

24. Basin volume [l]:

15

25. Tank power [kW]:

2.100

26. Number of arms for both rinsing and washing:

2

27. Arm connection:

Hand loosen/tighten screw

28. Washing arm type:

Rotatable two-pronged

Technical data sheet

Technical parameters



Hood type dishwasher single skin controls on TOP 50x50 - 400 V

Model	SAP Code	00011315
QQI 102/TOP	A group of articles - web	Undercounter, continuous and black ware dishwasher

29. Washing arm material:

Composite

30. Rinsing arm type:

Rotating two-pronged

31. Rinsing arm material:

Composite

32. Deep drawn tank:

Yes

33. Tank surface strainers:

composite

34. Drain filter:

ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

35. Thermostop:

Yes

36. Boiler thermostat adjust:

Yes

37. Rack feed capacity:

24-30-60

38. Detergent and rinse pump system:

ProDose - accurate dosing with a peristaltic pump

39. Energy Saving system:

EnergySaving - Energy saving system due to lowering the boiler temperature

40. Hot water electric valve:

Yes

41. Rack size [mm]:

500 x 500

42. Display type:

3 local display + diode bar

43. Location of control panel:

On the top

44. USB port:

Yes, for Firmware actualisation

45. Self-diagnostics:

Yes

46. Wash pump type:

two-way - DuoFlow

47. Detergent dispenser:

Yes

48. Rinse aid dispenser:

Yes

49. Water consumption of the washing cycle [l/basket]:

2,1

50. Washing cycle time [s/basket]:

60-120-150

51. Rinse water temperature [°C]:

80

52. Standard equipment for device:

1x glass basket, 1x plate basket, 1x cutlery basket

53. Program ProSpeed:

Yes

54. Program ProFessional:

Yes

Technical data sheet

Technical parameters



Hood type dishwasher single skin controls on TOP 50x50 - 400 V

Model	SAP Code	00011315
QQI 102/TOP	A group of articles - web	Undercounter, continuous and black ware dishwasher

55. Program ProTemp:

Yes

56. Program ProSelf:

Yes

57. Program ProLong:

Yes

58. Noise of device:

60,4

59. Cross-section of conductors CU [mm²]:

1,5

60. Water supply connection:

3/4"

61. Diameter nominal:

DN 50