Product features





Undercounter dishwasher double skin softener 40x40 - 230 V		
Model	SAP Code	00011284
NTA 42	A group of articles - web	Undercounter, continuous and black ware dishwasher




- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: ProScreen 4 digit display + 2 LED bars
- Number of programs: 6
- Number of skin: 2
- Door clear height [mm]: 320
- Rack size [mm]: 400 x 400
- Water consumption of the washing cycle [l/basket]: 1,9
- Washing cycle time [s/basket]: 90-120-150
- Detergent and rinse pump system: ProDose accurate dosing with a peristaltic pump
- Wash pump type: two-way DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes double filtration with overflow discharge ensures only 18% loss of clean water to waste

SAP Code	00011284	Boiler power [kW]	2.600
Net Width [mm]	466	Basin volume [l]	8
Net Depth [mm]	556	Tank power [kW]	0.600
Net Height [mm]	695	Water consumption of the washing cycle [l/basket]	1,9
Net Weight [kg]	47.00	Washing cycle time [s/basket]	90-120-150
Power electric [kW]	3.500	Door clear height [mm]	320
Loading	230 V / 1N - 50 Hz	Rack size [mm]	400 x 400
Boiler capacity [l]	2.60	Noise of device	54,3




Technical drawing

Undercounter dishwasher double skin softener 40x40 - 230 V		
Model	SAP Code	00011284
NTA 42	A group of articles - web	Undercounter, continuous and black ware dishwasher











Undercounter dishwasher double skin softener 40x40 - 230 V		
Model	SAP Code	00011284
NTA 42	A group of articles - web	Undercounter, continuous and black ware dishwasher

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

LED Display

proScreen 4 local display + 2 LED strips

Double pump
unique two-way DuoFlow pump

Molded basket supports
guide rails for the baskets molded from the body of the dishwasher

Detergent dispensers
two detergent and rinse aid dispensers

7 Double filter system
the chamber filter and the waste filter together with the
ArchiMedes system provide a discharge system with
increased water purification efficiency

Energy saving
energy saving energy saving system due to lowering the
temperature of the boiler

Protection of fragile dishes
softstart system for gradual start of washing programs to protect fragile dishes

Double shell construction

Fast heating

stainless steel construction with insulated double jacket

performance management allows the current running of the boiler and basins body



Technical parameters

Undercounter dishwasher double	e skin softener 40x40) - 230 V
Model	SAP Code	00011284
NTA 42	A group of articles - web	Undercounter, continuous and black ware dishwasher
1. SAP Code: 00011284		15. Number of programs:
2. Net Width [mm]: 466		16. Opening of device: Tilting down
3. Net Depth [mm]: 556		17. Door clear height [mm]: 320
4. Net Height [mm]: 695		18. Inlet pressure [bar]: 2-4
5. Net Weight [kg]: 47.00		19. Adjustable feet: Yes
6. Gross Width [mm]: 516		20. Number of skin:
7. Gross depth [mm]: 606		21. Self-cleaning cycle: Yes
8. Gross Height [mm]: 745		22. Boiler capacity [l]: 2.60
9. Gross Weight [kg]: 50.00		23. Boiler power [kW]: 2.600
10. Device type: Electric unit		24. Basin volume [l]:
11. Control type: Digital		25. Tank power [kW]: 0.600
12. Material: Stainless steel		26. Number of arms for both rinsing and washing:
13. Power electric [kW]: 3.500		27. Arm connection: Click-clack - easy removal with one hand

28. Washing arm type:

Rotatable two-pronged

14. Loading:

230 V / 1N - 50 Hz



Technical parameters

Undercounter dishwasher double	skin softener 40x40 -	· 230 V
Model	SAP Code	00011284
NTA 42	A group of articles - web	Undercounter, continuous and black ware dishwasher
29. Washing arm material: Composite		41. Heating system: HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle
30. Rinsing arm type: Rotating two-pronged		42. Hot water electric valve: Yes
31. Rinsing arm material: Composite		43. Closing door system: ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes
32. Deep drawn tank: Yes		44. Rack size [mm]: 400 × 400
33. Rack support: Pressed		45. Built-in softener: Yes
34. Tank surface strainers: composite		46. Display type: ProScreen - 4 digit display + 2 LED bars
35. Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste		47. USB port: Yes, for Firmware actualisation
36. Thermostop: Yes		48. Self-diagnostics:
37. Boiler thermostat adjust: Yes		49. Wash pump type: two-way - DuoFlow
38. Rack feed capacity: 24-30-40		50. Detergent dispenser: Yes
39. Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump		51. Rinse aid dispenser: Yes

1,9

52. Water consumption of the washing cycle [l/basket]:

40. Energy Saving system:

boiler temperature

EnergySaving - Energy saving system due to lowering the



Technical parameters

59. Program ProClean:

Yes

Undercounter dishwasher double skin softener 40x40 - 230 V		
Model	SAP Code	00011284
NTA 42	A group of articles - web	Undercounter, continuous and black ware dishwasher
53. Washing cycle time [s/basket]: 90-120-150		60. Program ProDrain: Yes
54. Rinse water temperature [°C]: 65		61. Program ProPlates: Yes
55. Standard equipment for device: 1x glass basket, 1x plate basket, 1x cutlery basket		62. Noise of device: 54,3
56. Program ProSpeed: Yes		63. Cross-section of conductors CU [mm²]:
57. Program ProFessional: Yes		64. Water supply connection: 3/4"
58. Program ProTemp: Yes		65. Diameter nominal: DN 50

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com