

Product features

Combi convection steam oven electric 7x GN 1/1 automatic cleaning extra, direct steam 400 V

 Model
 SAP Code
 00011354

- Steam type: Injection
- Number of GN / EN: 7
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Touchscreen + buttons
- Display size: 5"
- Humidity control: Yes, indirect measuring
- Advanced moisture adjustment: No
- Delta T heat preparation: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011354	Steam type	Injection
Net Width [mm]	870	Number of GN / EN	7
Net Depth [mm]	750	GN / EN size in device	GN 1/1
Net Height [mm]	820	GN device depth	65
Net Weight [kg]	95.00	Control type	Touchscreen + buttons
Power electric [kW]	12.600	Display size	5"
Loading	400 V / 3N - 50 Hz		



Product benefits

Combi convection steam oven electric 7x GN 1/1 automatic cleaning extra, direct steam 400 V

Model SAP Code 00011354

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets

Touch screen display simple intuitive control with unique pictograms,

all in Czech

the possibility of using preset programs or manual control

- help with cooking even for less skilled cooks
- the possibility of safe cooking even in the absence of the operator
- creating your own recipes

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

 allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously

Automatic washing

integrated chamber washing system the possibility of using liquid and tablet detergents option to use vinegar as a rinse aid the system also descales the micro boiler

 the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 100% hygienic quality

Six-speed reversible fan

ensures perfect distribution of steam without losing its saturation

its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed External temperature probe

temperature probe located outside the cooking area, option of choosing one point or vacuum probe

 positioning outside the cooking chamber extends its life; ensuring total food hygiene safety; HACCP record; control of heat treatment in the absence of the cook

USB

downloading service reports upgrade software playing recipes

- quick fault finding
- transfer of original recipes
- keeping software up to date

Temperature range 3°C - 3°C

heating the chamber in the temperature range of 30 to 300 $^{\circ}\text{C}$

 Possibility to prepare a large variety of dishes, from low-temperature baking to grilling, gratinating, etc.

Stainless steel construction

construction material is high quality stainless steel ensuring long life high hygiene standard

safe food preparation; long service life; easy cleaning

Reinforced version

reinforced heating elements in the chamber higher power input

Suitable for heavier workloads

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

2025-04-25

2



Technical parameters

Combi convection steam oven electric 7x GN 1/1 automatic cleaning extra, direct steam 400 V		
Model	SAP Code	00011354
1. SAP Code: 00011354		15. Adjustable feet: Yes
2. Net Width [mm]: 870		16. Humidity control: Yes, indirect measuring
3. Net Depth [mm]: 750		17. Stacking availability: Yes
4. Net Height [mm]: 820		18. Control type: Touchscreen + buttons
5. Net Weight [kg]: 95.00		19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)
6. Gross Width [mm]: 940		20. Steam type: Injection
7. Gross depth [mm]: 900		21. Sturdier version: Yes
8. Gross Height [mm]: 970		22. Chimney for moisture extraction: Yes
9. Gross Weight [kg]: 105.00		23. Delayed start: Yes
10. Device type: Electric unit		24. Display size: 5"
11. Power electric [kW]: 12.600		25. Delta T heat preparation: Yes
12. Loading: 400 V / 3N - 50 Hz		26. Unified finishing of meals EasyService: Yes
13. Material: AISI 304		27. Night cooking: Yes

28. Washing system:

Open

14. Exterior color of the device:

Stainless steel



Technical parameters

Combi convection steam oven electric 7x GN 1/1 automatic cleaning extra, direct steam 400 V			
Model SAP Code		00011354	
29. Detergent type: Liquid washing detergent + water rinse 30. Multi level cooking: Drawer program - control of heat treatment for each dish separately		43. Interior lighting: Yes	
		44. Low temperature heat treatment: Yes	
31. Advanced moisture adjustment:		45. Number of fans:	
32. Slow cooking: from 50 °C		46. Number of fan speeds: 3	
33. Fan stop: Interruption when door is opened, not braked		47. Number of programs: 1000	
34. Lighting type: LED lighting in the door, on one side		48. USB port: Yes, for uploading recipes and updating firmware	
35. Cavity material and shape: AISI 304, with rounded corners for easy cleaning		49. Door constitution: Vented safety double glass, removable for easy cleaning	
36. Reversible fan: Yes		50. Number of preset programs: 100	
37. Sustaince box: Yes		51. Number of recipe steps: 9	
38. Heating element material: Incoloy		52. Minimum device temperature [°C]:	
39. Probe: Optional		53. Maximum device temperature [°C]:	
40. Shower: Manual (optional)		54. Device heating type: Combination of steam and hot air	
41. Distance between the layers [mm]: 74		55. HACCP: Yes	
42. Smoke-dry function:		56. Number of GN / EN:	

Yes



Technical parameters

Combi convection steam oven electric 7x GN 1/1 automat			cleaning extra, direct steam 400 V	
Model SAP Code			00011354	
57. GN / EN size in device: GN 1/1			60. Cross-section of conductors CU [mm²]: 4	
58.	58. GN device depth: 65		61. Diameter nominal: DN 50	
59. Food regeneration: Yes			62. Water supply connection: 3/4"	