

| Combi convection steam oven electric 10x GN 1/1 automatic cleaning extra, direct steam 400 V | | |
|--|----------|--|
| Model | SAP Code | 00011358 |
| | | |
| | | |
| | | Steam type: Injection |
| | | – Number of GN / EN: 10 |
| | | – GN / EN size in device: GN 1/1 |
| | | – GN device depth: 65 |
| | | Control type: Touchscreen + buttons |
| | | – Display size: 5" |
| | | Humidity control: Yes, indirect measuring |
| | | Advanced moisture adjustment: No |
| | | Delta T heat preparation: Yes |
| | | Multi level cooking: Drawer program - control of heat treatment for each dish separately |
| | | Door constitution: Vented safety double glass, removable for easy cleaning |
| | | |
| | | |
| | | |

| SAP Code | 00011358 | Steam type | Injection |
|---------------------|--------------------|------------------------|-----------------------|
| Net Width [mm] | 870 | Number of GN / EN | 10 |
| Net Depth [mm] | 750 | GN / EN size in device | GN 1/1 |
| Net Height [mm] | 1050 | GN device depth | 65 |
| Net Weight [kg] | 100.00 | Control type | Touchscreen + buttons |
| Power electric [kW] | 17.300 | Display size | 5" |
| Loading | 400 V / 3N - 50 Hz | | |



Combi convection steam oven electric 10x GN 1/1 automatic cleaning extra, direct steam 400 V

Model

SAP Code

00011358



Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets

Touch screen display

simple intuitive control with unique pictograms, all in Czech

the possibility of using preset programs or manual control

- help with cooking even for less skilled cooks
- the possibility of safe cooking even in the absence of the operator
- creating your own recipes



A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

 allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously

Automatic washing

integrated chamber washing system the possibility of using liquid and tablet detergents option to use vinegar as a rinse aid the system also descales the micro boiler

 the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 100% hygienic quality

Six-speed reversible fan

ensures perfect distribution of steam without losing its saturation

its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed

6

External temperature probe

temperature probe located outside the cooking area, option of choosing one point or vacuum probe

 positioning outside the cooking chamber extends its life; ensuring total food hygiene safety; HACCP record; control of heat treatment in the absence of the cook

USB

downloading service reports upgrade software playing recipes

- quick fault finding
- transfer of original recipes
- keeping software up to date

Temperature range 3°C - 3°C

heating the chamber in the temperature range of 30 to 300 $^\circ\mathrm{C}$

- Possibility to prepare a large variety of dishes, from low-temperature baking to grilling, gratinating, etc.

Stainless steel construction

construction material is high quality stainless steel ensuring long life high hygiene standard

- safe food preparation; long service life; easy cleaning

Reinforced version

reinforced heating elements in the chamber higher power input

- Suitable for heavier workloads

10



| Combi convection steam oven e | lectric 10x GN 1/1 au | itomatic cleaning extra, direct steam 400 V |
|--|-----------------------|---|
| Model | SAP Code | 00011358 |
| | | |
| 1. SAP Code: 00011358 | | 15. Adjustable feet: Yes |
| 2. Net Width [mm]: | | 16. Humidity control: |
| 870 | | Yes, indirect measuring |
| 3. Net Depth [mm]: | | 17. Stacking availability: |
| 750 | | Yes |
| 4. Net Height [mm]: | | 18. Control type: |
| 1050 | | Touchscreen + buttons |
| 5. Net Weight [kg]: 100.00 | | 19. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering) |
| 6. Gross Width [mm]: | | 20. Steam type: |
| 940 | | Injection |
| 7. Gross depth [mm]: | | 21. Sturdier version: |
| 900 | | Yes |
| 8. Gross Height [mm]: | | 22. Chimney for moisture extraction: |
| 1160 | | Yes |
| 9. Gross Weight [kg]: | | 23. Delayed start: |
| 130.00 | | Yes |
| 10. Device type: Electric unit | | 24. Display size: 5" |
| 11. Power electric [kW]: | | 25. Delta T heat preparation: |
| 17.300 | | Yes |
| 12. Loading: | | 26. Unified finishing of meals EasyService: |
| 400 V / 3N - 50 Hz | | Yes |
| 13. Material: | | 27. Night cooking: |
| AISI 304 | | Yes |
| 14. Exterior color of the device: | | 28. Washing system: |
| Stainless steel | | Open |

Technical parameters



| Model SA | Code 00011358 |
|--|---|
| 9. Detergent type: | 43. Interior lighting: |
| Liquid washing detergent + water rinse | Yes |
| 0. Multi level cooking: Drawer program - control of heat treatm dish separately | ent for each Yes |
| 31. Advanced moisture adjustment: No | 45. Number of fans: 2 |
| 32. Slow cooking: | 46. Number of fan speeds: |
| from 50 °C | 3 |
| 33. Fan stop: | 47. Number of programs: |
| Interruption when door is opened, not b | 1000 |
| 34. Lighting type: | 48. USB port: |
| LED lighting in the door, on one side | Yes, for uploading recipes and updating firmware |
| 35. Cavity material and shape: | 49. Door constitution: |
| AISI 304, with rounded corners for easy o | leaning Vented safety double glass, removable for easy cleaning |
| 36. Reversible fan: Yes | 50. Number of preset programs: 100 |
| 37. Sustaince box: | 51. Number of recipe steps: |
| Yes | 9 |
| 38. Heating element material: Incoloy | 52. Minimum device temperature [°C]: |
| 39. Probe: | 53. Maximum device temperature [°C]: |
| Optional | 300 |
| 40. Shower: | 54. Device heating type: |
| Manual (optional) | Combination of steam and hot air |
| 1. Distance between the layers [mm]: 74 | 55. HACCP: Yes |
| 42. Smoke-dry function: | 56. Number of GN / EN: |
| Yes | 10 |

4



| Combi convection steam oven electric 10x GN 1/1 automatic cleaning extra, direct steam 400 V | | | | |
|--|----------|--------------------------------------|--|--|
| Model | SAP Code | 00011358 | | |
| | | | | |
| | | | | |
| 57. GN / EN size in device: GN 1/1 | | 59. Food regeneration: Yes | | |
| 58. GN device depth: | | | | |
| - 65 | | | | |

2024-07-05