

Technical data sheet

Product features



Blast chiller/freezer 10x GN 1/1 digital control panel PET 230 V

Model	SAP Code	00010008
SHF 1011	A group of articles - web	Šokery a multifunkční zařízení



- Shock cooling cycle kg / min (+3 ° C): 32
- Shock freeze cycle kg / min (-18 ° C): 22
- Minimum device temperature [°C]: 3
- Maximum device temperature [°C]: -18
- Probe: 4-points
- Insulation thickness [mm]: 60
- Control type: Digital

SAP Code	00010008	Number of GN / EN	10
Net Width [mm]	790	GN / EN size in device	GN 1/1
Net Depth [mm]	799	GN device depth	40
Net Height [mm]	1629	Shock cooling cycle kg / min (+3 ° C)	32
Net Weight [kg]	129.00	Shock freeze cycle kg / min (-18 ° C)	22
Power electric [kW]	0.900	Control type	Digital
Loading	230 V / 1N - 50 Hz		


Technical data sheet

Technical drawing



Blast chiller/freezer 10x GN 1/1 digital control panel PET 230 V

Model	SAP Code	00010008
SHF 1011	A group of articles - web	Šokery a multifunkční zařízení



Technical data sheet



Product benefits

Blast chiller/freezer 10x GN 1/1 digital control panel PET 230 V

Model	SAP Code	00010008
SHF 1011	A group of articles - web	Šokery a multifunkční zařízení

1

Very fast cooling and freezing

times faster cooling and freezing compared to a classic refrigerator/freezer

2

Controlled defrosting

safety and hygiene

3

Probe in standard equipment

accurate and safe cooling/freezing/defrosting thanks to core temperature measurement

4

Digital control

clarity and simplicity of operation

5

Autorepair surface

easy to maintain

Technical data sheet

Technical parameters



Blast chiller/freezer 10x GN 1/1 digital control panel PET 230 V

Model	SAP Code	00010008
SHF 1011	A group of articles - web	Šokery a multifunkční zařízení

1. SAP Code:

00010008

2. Net Width [mm]:

790

3. Net Depth [mm]:

799

4. Net Height [mm]:

1629

5. Net Weight [kg]:

129.00

6. Gross Width [mm]:

830

7. Gross depth [mm]:

860

8. Gross Height [mm]:

1780

9. Gross Weight [kg]:

139.60

10. Device type:

Electric unit

11. Opening of device:

Hinges on the left

12. Power electric [kW]:

0.900

13. Loading:

230 V / 1N - 50 Hz

14. Control type:

Digital

15. Refrigerant:

R452a

16. Number of GN / EN:

10

17. GN / EN size in device:

GN 1/1

18. GN device depth:

40

19. Minimum device temperature [°C]:

3

20. Maximum device temperature [°C]:

-18

21. Shock freeze cycle kg / min (-18 ° C):

22

22. Shock cooling cycle kg / min (+3 ° C):

32

23. Insulation thickness [mm]:

60

24. Probe:

4-points

25. Adjustable feet:

Yes

26. Cross-section of conductors CU [mm²]:

0,5