

Technical data sheet

Product features



Undercounter dishwasher double skin 50x50 - 400 V

Model	SAP Code	00011288
NT 52 TB	A group of articles - web	Undercounter, continuous and black ware dishwasher



- To the product for free: 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273)
- Display type: ProScreen - 4 digit display + 2 LED bars
- Number of programs: 7
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle [l/basket]: 1,8
- Washing cycle time [s/basket]: 60-90-180
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

SAP Code	00011288	Boiler power [kW]	6.000
Net Width [mm]	600	Basin volume [l]	15
Net Depth [mm]	600	Tank power [kW]	1.400
Net Height [mm]	1250	Water consumption of the washing cycle [l/basket]	1,8
Net Weight [kg]	63.00	Washing cycle time [s/basket]	60-90-180
Power electric [kW]	7.900	Door clear height [mm]	465
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [l]	6.00	Noise of device	59,4


Technical data sheet

Technical drawing



Undercounter dishwasher double skin 50x50 - 400 V

Model	SAP Code	00011288
NT 52 TB	A group of articles - web	Undercounter, continuous and black ware dishwasher



Technical data sheet

Product benefits



Undercounter dishwasher double skin 50x50 - 400 V

Model	SAP Code	00011288
NT 52 TB	A group of articles - web	Undercounter, continuous and black ware dishwasher

1

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

2

Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

3

LED Display

proScreen 4 local display + 2 LED strips

4

Double pump

unique two-way DuoFlow pump

5

Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

6

Detergent dispensers

two detergent and rinse aid dispensers

7

Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

8

Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

9

Protection of fragile dishes

softstart system for gradual start of washing programs to protect fragile dishes

10

Double shell construction

stainless steel construction with insulated double jacket

11

Fast heating

performance management allows the current running of the boiler and basins body

Technical data sheet

Technical parameters



Undercounter dishwasher double skin 50x50 - 400 V

Model	SAP Code	00011288
NT 52 TB	A group of articles - web	Undercounter, continuous and black ware dishwasher

1. SAP Code:

00011288

2. Net Width [mm]:

600

3. Net Depth [mm]:

600

4. Net Height [mm]:

1250

5. Net Weight [kg]:

63.00

6. Gross Width [mm]:

650

7. Gross depth [mm]:

650

8. Gross Height [mm]:

1300

9. Gross Weight [kg]:

69.00

10. Device type:

Electric unit

11. Control type:

Digital

12. Material:

Stainless steel

13. Power electric [kW]:

7.900

14. Loading:

400 V / 3N - 50 Hz

15. Number of programs:

7

16. Opening of device:

Tilting down

17. Door clear height [mm]:

465

18. Inlet pressure [bar]:

2-4

19. Adjustable feet:

Yes

20. Number of skin:

2

21. Self-cleaning cycle:

Yes

22. Boiler capacity [l]:

6.00

23. Boiler power [kW]:

6.000

24. Basin volume [l]:

15

25. Tank power [kW]:

1.400

26. Number of arms for both rinsing and washing:

2

27. Arm connection:

Click-clack - easy removal with one hand

28. Washing arm type:

Rotatable two-pronged

Technical data sheet

Technical parameters



Undercounter dishwasher double skin 50x50 - 400 V

Model	SAP Code	00011288
NT 52 TB	A group of articles - web	Undercounter, continuous and black ware dishwasher

29. Washing arm material:

Composite

30. Rinsing arm type:

Rotating two-pronged

31. Rinsing arm material:

Composite

32. Deep drawn tank:

Yes

33. Rack support:

Pressed

34. Tank surface strainers:

composite

35. Drain filter:

ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

36. Thermostop:

Yes

37. Boiler thermostat adjust:

Yes

38. Rack feed capacity:

60-40-20

39. Detergent and rinse pump system:

ProDose - accurate dosing with a peristaltic pump

40. Energy Saving system:

EnergySaving - Energy saving system due to lowering the boiler temperature

41. Heating system:

HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

42. Hot water electric valve:

Yes

43. Closing door system:

ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes

44. Rack size [mm]:

500 x 500

45. Display type:

ProScreen - 4 digit display + 2 LED bars

46. USB port:

Yes, for Firmware actualisation

47. Self-diagnostics:

Yes

48. Wash pump type:

two-way - DuoFlow

49. Detergent dispenser:

Yes

50. Rinse aid dispenser:

Yes

51. Water consumption of the washing cycle [l/basket]:

1,8

52. Washing cycle time [s/basket]:

60-90-180

Technical data sheet

Technical parameters



Undercounter dishwasher double skin 50x50 - 400 V

Model	SAP Code	00011288
NT 52 TB	A group of articles - web	Undercounter, continuous and black ware dishwasher

53. Rinse water temperature [°C]:

80

54. Standard equipment for device:

1x glass basket, 1x plate basket, 1x cutlery basket

55. Program ProSpeed:

Yes

56. Program ProFessional:

Yes

57. Program ProTemp:

Yes

58. Program ProSelf:

Yes

59. Program ProEco:

Yes

60. Program ProLong:

Yes

61. Program ProGlass:

Yes

62. Noise of device:

59,4

63. Cross-section of conductors CU [mm²]:

1,5

64. Water supply connection:

3/4"

65. Diameter nominal:

DN 50