

Technical data sheet

Product features



Pastry oven digital 4x GN 1/1 - 6,3 kW

Model	SAP Code	00008425
--------------	-----------------	----------



- Material: AISI 304
- Control type: Digital
- Chimney for moisture extraction: No
- Adjustable chimney: Yes

SAP Code	00008425	Net Weight [kg]	63.00
Net Width [mm]	770	Power electric [kW]	6.300
Net Depth [mm]	740	Loading	400 V / 3N - 50 Hz
Net Height [mm]	675		

Technical data sheet

Product benefits



Pastry oven digital 4x GN 1/1 - 6,3 kW

Model

SAP Code

00008425

1

All-stainless steel construction

round construction with stainless steel, rounded edges

- easy cleaning, high hygiene standard, long service life

2

Digital display

simple multi-line backlit display of 99 programs with 10 degrees of humidification

- help with cooking even for less skilled cooks, safe baking even in the absence of an operator; create your own recipes; easy to use

3

Double loading insert, transverse

inserts shaped from rigid stainless steel wire allowing insertion of GN or baking trays

- the possibility of baking on baking trays or gastronomes

4

Moisturizing

steam generation using direct injection

- baking with moistening, lighter doughs, battered doughs

5

Reverse fan

the fan changes direction of rotation at regular intervals perfectly ventilates the entire space

- allows baking of desserts and doughs without the need to turn them

Technical data sheet

Technical parameters



Pastry oven digital 4x GN 1/1 - 6,3 kW

Model

SAP Code

00008425

1. SAP Code:

00008425

2. Net Width [mm]:

770

3. Net Depth [mm]:

740

4. Net Height [mm]:

675

5. Net Weight [kg]:

63.00

6. Gross Width [mm]:

875

7. Gross depth [mm]:

870

8. Gross Height [mm]:

860

9. Gross Weight [kg]:

73.00

10. Exterior color of the device:

Stainless steel

11. Material:

AISI 304

12. Device type:

Electric unit

13. Power electric [kW]:

6.300

14. Loading:

400 V / 3N - 50 Hz

15. Control type:

Digital

16. Chimney for moisture extraction:

No

17. Adjustable chimney:

Yes

18. Cross-section of conductors CU [mm²]:

0,75

- Výkon (kW): 3,3-3,7 (230 V)