

# Technical data sheet

Product features



## Freezing counter 2 chambers GN 1/1, unit left with splash back

<b>Model</b>	<b>SAP Code</b>	00020355
--------------	-----------------	----------

- Material: AISI 304
- GN / EN size in device: GN 1/1
- Control type: Digital
- Minimum device temperature [°C]: -18
- Maximum device temperature [°C]: -24
- Max ambient temperature [°C]: 43
- Insulation thickness [mm]: 70
- Unit: Left

<b>SAP Code</b>	00020355	<b>Loading</b>	230 V / 1N - 50 Hz
<b>Net Width [mm]</b>	1380	<b>GN / EN size in device</b>	GN 1/1
<b>Net Depth [mm]</b>	700	<b>Minimum device temperature [°C]</b>	-18
<b>Net Height [mm]</b>	850	<b>Maximum device temperature [°C]</b>	-24
<b>Net Weight [kg]</b>	110.00	<b>Refrigerant</b>	R290
<b>Power electric [kW]</b>	0.320		

# Technical data sheet

Technical parameters



## Freezing counter 2 chambers GN 1/1, unit left with splash back

Model	SAP Code	00020355
-------	----------	----------

**1. SAP Code:**

00020355

**15. Material:**

AISI 304

**2. Net Width [mm]:**

1380

**16. Min ambient temperature [°C]:**

10

**3. Net Depth [mm]:**

700

**17. Max ambient temperature [°C]:**

43

**4. Net Height [mm]:**

850

**18. Device properties 2:**

Freezing

**5. Net Weight [kg]:**

110.00

**19. GN / EN size in device:**

GN 1/1

**6. Gross Width [mm]:**

1450

**20. Adjustable feet:**

Yes

**7. Gross depth [mm]:**

750

**21. Insulation thickness [mm]:**

70

**8. Gross Height [mm]:**

900

**22. Gasket:**

Yes

**9. Gross Weight [kg]:**

130.00

**23. Unit:**

Left

**10. Device type:**

Electric unit

**24. Control type:**

Digital

**11. Power electric [kW]:**

0.320

**25. Minimum device temperature [°C]:**

-18

**12. Loading:**

230 V / 1N - 50 Hz

**26. Maximum device temperature [°C]:**

-24

**13. Refrigerant:**

R290

**27. Gross Volume [m3]:**

0.979

**14. Cooling type:**

Dinamic

**28. Net Volume [m3]:**

0.821

# Technical data sheet

Technical parameters



Freezing counter 2 chambers GN 1/1, unit left with splash back

Model

SAP Code

00020355

## 29. Cross-section of conductors CU [mm<sup>2</sup>]:

0,5

– Výkon (kW): 2,4-3,3 (230 V)