Technical data sheet



Product features

Conveyor toaster 2x holders

Model

SAP Code

00004520



- Material: Stainless steel
- Indicators: operation and warm-up
- Removable rear wall of the device: Yes
- Width of internal part [mm]: 305
- Depth of internal part [mm]: 500
- Heating location: Upper and lower

| SAP Code | 00004520 | Net Weight [kg] | 21.00 |
|-----------------|----------|---------------------|--------------------|
| Net Width [mm] | 490 | Power electric [kW] | 3.200 |
| Net Depth [mm] | 540 | Loading | 230 V / 1N - 50 Hz |
| Net Height [mm] | 400 | | |

Technical data sheet



Product benefits

| Conveyor toaster 2x holders | | | | |
|-----------------------------|----------|----------|--|--|
| Model | SAP Code | 00004520 | | |

All-stainless design

only stainless steel intended for food contact is used

- absolutely rust-proof and non-magnetic design resists even weak acids easier compliance with hygiene standards (HACCP); easy maintenance and cleaning
- Run and warm-up light

optical possibility to check the status of the device

- the operator immediately knows the on/off, heating/ non-heating state of the appliance
- Separate control for individual sections
 - the possibility of a heating system separately
 - greater variability of use
 - **Catch container for breadcrumbs**

breadcrumbs fall outside the furnace

- no crumbs falling off
- Removable back wall

- possibility to open the back wall of the device
- possible filling of the equipment by the operator
- **Continuous toaster** automatic toast advance
 - greater capacity
- **Silicon heaters** immediate onset of heat intense radiant heat
 - the device can be switched off even during the operating day
 - toasted food vigorously and without overheating inside
 - faster food preparation

Technical data sheet



Technical parameters

| Conveyor toaster 2x holders | | |
|---|----------|---|
| Model | SAP Code | 00004520 |
| | | |
| 1. SAP Code: 00004520 | | 13. Power electric [kW]: 3.200 |
| 2. Net Width [mm]: 490 | | 14. Loading: 230 V / 1N - 50 Hz |
| 3. Net Depth [mm]: 540 | | 15. Heating element material: Silicon tube |
| 4. Net Height [mm]: 400 | | 16. Protection of controls: |
| 5. Net Weight [kg]: 21.00 | | 17. Toasting time: |
| 6. Gross Width [mm]: 515 | | 18. Removable rear wall of the device: Yes |
| 7. Gross depth [mm]: 750 | | 19. Indicators: operation and warm-up |
| 8. Gross Height [mm]: 440 | | 20. Width of internal part [mm]: 305 |
| 9. Gross Weight [kg]: 22.00 | | 21. Depth of internal part [mm]: 500 |
| 10. Device type: Electric unit | | 22. Heating location: Upper and lower |
| 11. Construction type of device: Table top | | 23. Cross-section of conductors CU [mm²]: 0,75 - Výkon (kW): 3,3-3,7 (230 V) |
| | | |

12. Material:

Stainless steel