

#### **Product features**

Combi convection steam oven electric 7x GN 1/1 automatic cleaning extra, direct steam 400 V		
Model	SAP Code	00011354
EPD X 0711 EAM	A group of articles - web	Convection machines
		<ul><li>Steam type: Injection</li></ul>

-	Steam type: Injection
_	Number of GN / EN: 7
_	GN / EN size in device: GN 1/1
_	GN device depth: 65

- Control type: Touchscreen + buttons
- Display size: 5"
- Humidity control: Yes, indirect measuring
- Advanced moisture adjustment: No
- Delta T heat preparation: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011354	Steam type	Injection
Net Width [mm]	870	Number of GN / EN	7
Net Depth [mm]	750	GN / EN size in device	GN 1/1
Net Height [mm]	820	GN device depth	65
Net Weight [kg]	95.00	Control type	Touchscreen + buttons
Power electric [kW]	12.600	Display size	5"
Loading	400 V / 3N - 50 Hz		



#### **Product benefits**

Combi convection steam oven electric 7x GN 1/1 automatic cleaning extra, direct steam 400 V		
Model	SAP Code	00011354
EPD X 0711 EAM	A group of articles - web	Convection machines

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

Touch screen display

simple intuitive control with unique pictograms, all in Czech

the possibility of using preset programs or manual control  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left$ 

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

**Automatic washing** 

integrated chamber washing system the possibility of using liquid and tablet detergents option to use vinegar as a rinse aid the system also descales the micro boiler

Six-speed reversible fan

ensures perfect distribution of steam without losing its saturation

its operation is controlled by the program or manually

**External temperature probe** 

temperature probe located outside the cooking area, option of choosing one point or vacuum probe

\_\_ USB

downloading service reports upgrade software playing recipes Temperature range 3°C - 3°C

heating the chamber in the temperature range of 30 to 300  $^{\circ}\text{C}$ 

Stainless steel construction

construction material is high quality stainless steel ensuring long life

high hygiene standard

Reinforced version

reinforced heating elements in the chamber higher power input



#### Technical parameters

Combi convection steam over	ı electric 7x GN 1/1 autoı	matic cleaning extra, direct steam 400 V
Model	SAP Code	00011354
EPD X 0711 EAM	A group of articles - web	Convection machines
<b>1. SAP Code:</b> 00011354		<b>15. Adjustable feet:</b> Yes
2. Net Width [mm]: 870		<b>16. Humidity control:</b> Yes, indirect measuring
<b>3. Net Depth [mm]:</b> 750		<b>17. Stacking availability:</b> Yes
<b>4. Net Height [mm]:</b> 820		<b>18. Control type:</b> Touchscreen + buttons
<b>5. Net Weight [kg]:</b> 95.00		19. Additional information:  possibility of reverse door opening - handle on the right side (must be specified when ordering)
<b>6. Gross Width [mm]:</b> 940		20. Steam type: Injection
<b>7. Gross depth [mm]:</b> 900		<b>21. Sturdier version:</b> Yes
8. Gross Height [mm]: 970		<b>22. Chimney for moisture extraction:</b> Yes
9. Gross Weight [kg]: 105.00		23. Delayed start: Yes
10. Device type: Electric unit		<b>24. Display size:</b> 5"
11. Power electric [kW]: 12.600		25. Delta T heat preparation: Yes
<b>12. Loading:</b> 400 V / 3N - 50 Hz		<b>26. Unified finishing of meals EasyService:</b> Yes
13. Material: AISI 304		27. Night cooking: Yes
14. Exterior color of the device:		28. Washing system:

Open

Stainless steel



### Technical parameters

Combi convection steam oven	electric 7x GN 1/1 autor	matic cleaning extra, direct steam 400 V
Model	SAP Code	00011354
EPD X 0711 EAM	A group of articles - web	Convection machines
29. Detergent type: Liquid washing detergent + wat	er rinse	<b>43. Interior lighting:</b> Yes
<b>30. Multi level cooking:</b> Drawer program - control of headish separately	at treatment for each	<b>44. Low temperature heat treatment:</b> Yes
31. Advanced moisture adjustme	ent:	45. Number of fans:
<b>32. Slow cooking:</b> from 50 °C		<b>46. Number of fan speeds:</b> 3
<b>33. Fan stop:</b> Interruption when door is open	ed, not braked	<b>47. Number of programs:</b> 1000
<b>34. Lighting type:</b> LED lighting in the door, on one	e side	<b>48. USB port:</b> Yes, for uploading recipes and updating firmware
<b>35. Cavity material and shape:</b> AISI 304, with rounded corners	for easy cleaning	<b>49. Door constitution:</b> Vented safety double glass, removable for easy cleaning
<b>36. Reversible fan:</b> Yes		<b>50. Number of preset programs:</b> 100
<b>37. Sustaince box:</b> Yes		<b>51. Number of recipe steps:</b> 9
38. Heating element material: Incoloy		<b>52. Minimum device temperature [°C]:</b> 50
<b>39. Probe:</b> Optional		<b>53. Maximum device temperature [°C]:</b> 300
<b>40. Shower:</b> Manual (optional)		<b>54. Device heating type:</b> Combination of steam and hot air
<b>41. Distance between the layers [mm]:</b> 74		55. HACCP: Yes
42. Smoke-dry function:		56. Number of GN / EN:

Yes



### Technical parameters

Combi convection steam oven electric 7x GN 1/1 automatic cleaning extra, direct steam 400 V		
Model	SAP Code	00011354
EPD X 0711 EAM	A group of articles - web	Convection machines
<b>57. GN / EN size in device:</b> GN 1/1		60. Cross-section of conductors CU [mm <sup>2</sup> ]:
-		

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com