



Undercounter dishwasher double skin softener 40x40 - 230 V

Model SAP Code 00011284



- Display type: ProScreen 4 digit display + 2 LED bars
- Number of programs: 6
- Number of skin: 2
- Door clear height [mm]: 320
- Rack size [mm]: 400 x 400
- Water consumption of the washing cycle [l/basket]: 1,9
- Washing cycle time [s/basket]: 90-120-150
- Detergent and rinse pump system: ProDose accurate dosing with a peristaltic pump
- Wash pump type: two-way DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes double filtration with overflow discharge ensures only 18% loss of clean water to waste


SAP Code	00011284	Boiler power [kW]	2.600
Net Width [mm]	466	Basin volume [l]	8
Net Depth [mm]	556	Tank power [kW]	0.600
Net Height [mm]	695	Water consumption of the washing cycle [l/basket]	1,9
Net Weight [kg]	47.00	Washing cycle time [s/basket]	90-120-150
Power electric [kW]	3.500	Door clear height [mm]	320
Loading	230 V / 1N - 50 Hz	Rack size [mm]	400 x 400
Boiler capacity [l]	2.60	Noise of device	54,3




Technical drawing

Undercounter dishwasher double skin softener 40x40 - 230 V

Model SAP Code 00011284





320

295

Product benefits



Undercounter dishwasher double skin softener 40x40 - 230 V

Model SAP Code 00011284

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

easy cleaning, high hygiene standard, long service life

Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

easy and safe handling during cleaning; higher user comfort

LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

Double pump

unique two-way DuoFlow pump

 distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

Detergent dispensers

two detergent and rinse aid dispensers

 precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

higher washing efficiency; longer life of the washing bath

Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

cost saving

Protection of fragile dishes

softstart system for gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

Double shell construction

stainless steel construction with insulated double jacket

- quiet operation
- energy saving

Fast heating

performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

2024-07-30

3



Technical parameters

Undercounter dishwasher double skin softener 40x40 - 230 V				
Model	SAP Code	00011284		
1. SAP Code: 00011284		15. Number of programs: 6		
2. Net Width [mm]: 466		16. Opening of device: Tilting down		
3. Net Depth [mm]: 556		17. Door clear height [mm]: 320		
4. Net Height [mm]: 695		18. Inlet pressure [bar]: 2-4		
5. Net Weight [kg]: 47.00		19. Adjustable feet: Yes		
6. Gross Width [mm]: 516		20. Number of skin:		
7. Gross depth [mm]: 606		21. Self-cleaning cycle: Yes		
8. Gross Height [mm]: 745		22. Boiler capacity [l]: 2.60		
9. Gross Weight [kg]: 50.00		23. Boiler power [kW]: 2.600		
10. Device type: Electric unit		24. Basin volume [l]:		
11. Control type: Digital		25. Tank power [kW]: 0.600		
12. Material: Stainless steel		26. Number of arms for both rinsing and washing:		
13. Power electric [kW]: 3.500		27. Arm connection: Click-clack - easy removal with one hand		

28. Washing arm type:

Rotatable two-pronged

14. Loading:

230 V / 1N - 50 Hz



Undercounter dishwasher double skin softener 40x40 - 230 V				
Model	SAP Code	00011284		

Technical parameters

Composite

30. Rinsing arm type:

Rotating two-pronged

31. Rinsing arm material:

Composite

32. Deep drawn tank:

Yes

33. Rack support:

Pressed

34. Tank surface strainers:

composite

35. Drain filter:

ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

36. Thermostop:

Yes

37. Boiler thermostat adjust:

Yes

38. Rack feed capacity:

24-30-40

39. Detergent and rinse pump system:

ProDose - accurate dosing with a peristaltic pump

40. Energy Saving system:

EnergySaving - Energy saving system due to lowering the boiler temperature

41. Heating system:

HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

42. Hot water electric valve:

43. Closing door system:

ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes

44. Rack size [mm]:

400 x 400

45. Built-in softener:

46. Display type:

ProScreen - 4 digit display + 2 LED bars

47. USB port:

Yes, for Firmware actualisation

48. Self-diagnostics:

Yes

49. Wash pump type:

two-way - DuoFlow

50. Detergent dispenser:

51. Rinse aid dispenser:

52. Water consumption of the washing cycle [l/basket]:

1,9



Technical parameters

58. Program ProFessional:

Yes

Undercounter dishwasher double skin softener 40x40 - 230 V				
Model	SAP Code	00011284		
53. Washing cycle time [s/basket]:		59. Program ProTemp:		
90-120-150		Yes 		
54. Rinse water temperature [°C]: 65		60. Program ProClean: Yes		
55. Standard equipment for device: 1x glass basket, 1x plate basket, 1x cutlery basket		61. Program ProDrain: Yes		
56. Additional information: The product comes with 1x RM Clea and 1x RM Rinse+ 10 kg (00012273) f	0 1	62. Program ProPlates: Yes		
57. Program ProSpeed: Yes		63. Noise of device: 54,3		

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com