

Technical data sheet

Product features



Electric freezer tabletop 850mm GN1/1, 2 doors, with hatch, agr. left stainless steel 230V OOP

Model	SAP Code	00020355
SM 2D DL GI	A group of articles - web	Cooling and freezing tables

- Material: AISI 304
- GN / EN size in device: GN 1/1
- Control type: Digital
- Minimum device temperature [°C]: -18
- Maximum device temperature [°C]: -24
- Max ambient temperature [°C]: 43
- Insulation thickness [mm]: 70
- Unit: Left

SAP Code	00020355	Loading	230 V / 1N - 50 Hz
Net Width [mm]	1380	GN / EN size in device	GN 1/1
Net Depth [mm]	700	Minimum device temperature [°C]	-18
Net Height [mm]	850	Maximum device temperature [°C]	-24
Net Weight [kg]	110.00	Refrigerant	R290
Power electric [kW]	0.320		

Technical data sheet

Technical parameters



Electric freezer tabletop 850mm GN1/1, 2 doors, with hatch, agr. left stainless steel 230V OOP

Model	SAP Code	00020355
SM 2D DL GI	A group of articles - web	Cooling and freezing tables

1. SAP Code:

00020355

2. Net Width [mm]:

1380

3. Net Depth [mm]:

700

4. Net Height [mm]:

850

5. Net Weight [kg]:

110.00

6. Gross Width [mm]:

1450

7. Gross depth [mm]:

750

8. Gross Height [mm]:

900

9. Gross Weight [kg]:

130.00

10. Device type:

Electric unit

11. Power electric [kW]:

0.320

12. Loading:

230 V / 1N - 50 Hz

13. Refrigerant:

R290

14. Cooling type:

Dinamic

15. Material:

AISI 304

16. Min ambient temperature [°C]:

10

17. Max ambient temperature [°C]:

43

18. Device properties 2:

Freezing

19. GN / EN size in device:

GN 1/1

20. Adjustable feet:

Yes

21. Insulation thickness [mm]:

70

22. Gasket:

Yes

23. Unit:

Left

24. Control type:

Digital

25. Minimum device temperature [°C]:

-18

26. Maximum device temperature [°C]:

-24

27. Gross Volume [m3]:

0.979

28. Net Volume [m3]:

0.821

Technical data sheet

Technical parameters



Electric freezer tabletop 850mm GN1/1, 2 doors, with hatch, agr. left stainless steel 230V OOP

Model	SAP Code	00020355
SM 2D DL GI	A group of articles - web	Cooling and freezing tables

29. Cross-section of conductors CU [mm²]:

0,5