

Product features

Boiling kettle electric indirect 150 l

Model SAP Code 00011718



- Device type: Electric unit
- Device heating type: Indirect
- Steam pressure regulation: Mechanical the valve releases steam at high pressure
- Filling: Mechanical cock
- Jacket filling: Semi-automatic
- Drain: Yes
- Drain valve diameter: 2"
- Basin volume [l]: 150
- Usable volume [l]: 134


SAP Code	00011718	Loading	400 V / 3N - 50 Hz
Net Width [mm]	800	Basin volume [l]	150
Net Depth [mm]	900	Usable volume [l]	134
Net Height [mm]	900	Device heating type	Indirect
Net Weight [kg]	150.00	Steam pressure regulation	Mechanical - the valve releases steam at high pressure
Power electric [kW]	21.000		mgn pressure





Technical drawing

Boiling kettle electric indirect 150 l

Model SAP Code 00011718









Product benefits

Boiling kettle electric indirect 150 l

Model SAP Code 00011718

Semi-automatic tolerance

maintenance-free system the absence of a probe that can become calcified long life

- savings on service interventions
- avoidance of losses due to interruption of plant operation

Degree of protection of the control elements IPX4

maintenance-free system resistance to splash water long life

- savings on service interventions
- easy cleaning and maintenance of equipment

Smart handle protection against scalding when lifting the lid

easy handling to operate at any height

- high security
- fewer health problems caused by poor ergonomics

Duplicator bottom AISI 316

long service life even in an aggressive salty environment

- savings on service interventions
- avoidance of losses due to interruption of plant operation

All-stainless design including bottom

long service life even in an aggressive salty environment

- savings on service interventions
- easy cleaning and maintenance of equipment

Top pressed plate

it prevents overflowing liquid from running into the controls or onto the operator's feet

- eliminates problems with possible malfunctions
- increases user comfort



Technical parameters

Boiling kettle electric indirect 150 l	
Model S.	AP Code 00011718
1. SAP Code: 00011718	15. Material: AISI 304 top plate, AISI 430 cladding
2. Net Width [mm]: 800	16. Indicators: operation and warm-up
3. Net Depth [mm]: 900	17. Drain valve diameter:
4. Net Height [mm]: 900	18. Worktop type: Molded - comfortable cleaning maintenance
5. Net Weight [kg]: 150.00	19. Worktop Thickness [mm]: 1.50
6. Gross Width [mm]: 970	20. Device heating type: Indirect
7. Gross depth [mm]: 840	21. Basin volume [l]: 150
8. Gross Height [mm]: 1160	22. Service accessibility: Trough the frontal panel
9. Gross Weight [kg]: 173.00	23. Safety thermostat: Yes
10. Device type: Electric unit	24. Adjustable feet: Yes
11. Construction type of device: With substructure	25. Bottom material: AISI 316
12. Power electric [kW]: 21.000	26. Usable volume [l]: 134
13. Loading: 400 V / 3N - 50 Hz	27. Filling: Mechanical cock

IPX4

14. Protection of controls:

28. Jacket filling:

Semi-automatic



Technical parameters

Boiling kettle electric indirect 150 l				
Model	SAP Code	00011718		
29. Steam pressure regulation: Mechanical - the valve releases steam at high pressure		33. Water filling type: Cold		
30. Type of drain valve: conical		34. Drain: Yes		
31. Overflow: Yes		35. Cross-section of conductors CU [mm²]:		
32. Manometer: Yes		36. Water supply connection: 1/2"		