



Combi convection steam oven STEAMBOX electric 10x GN 1/1 touch screen automatic cleaning direct steam 400 V

Model SAP Code 00011593

- Steam type: Injection
- Number of GN / EN: 10
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Digital
- Humidity control: MeteoSystem regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Supersteam two steam saturation modes
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: No
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011593	Loading	400 V / 3N - 50 Hz
Net Width [mm]	860	Steam type	Injection
Net Depth [mm]	795	Number of GN / EN	10
Net Height [mm]	1115	GN / EN size in device	GN 1/1
Net Weight [kg]	168.00	GN device depth	65
Power electric [kW]	15.700	Control type	Digital

Product benefits



Combi convection steam oven STEAMBOX electric 10x GN 1/1 touch screen automatic cleaning direct steam 400 V

Model **SAP Code** 00011593

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets

Digital display

simple multi-line backlit display of 99 programs with 9 cooking phases

- help with cooking even for less skilled cooks, safe baking even in the absence of an operator; create your own recipes; easy to use

Weather system

patented device for measuring steam saturation in real time and in steam mode, the only one on the market

- precise information for the operator about the steam saturation in the cooking area

Steam tuner

a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process

 possibility of cooking different types of cuisine, from very moist steam for typical Czech dishes to lowsaturated steam for e.g. French cuisine

Pass-through door

the door is also built into the back of the combi oven. while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen

- the chef can dispense the food through the convecto machine, the customer can see the preparation and maintenance of the food during dispensing

Adaptation for roasting chickens

the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat

- grease does not drain into the sewer, does not destroy the machine's waste system

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

 allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously

Premix burner

the only burner with a turbo pre-mixing gas with air on the market

the structure of the burner to V which prevents backfill and banging

This design saves 30 % of gas compared to conventional burners

faster heat-up faster more comfortable operation

Automatic washing

integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler

- the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 1% hygienic quality

Self-supporting shower

drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed

- allows food in the food processor to be rinsed out - if necessary to speed up cooling

Six-speed fan, reversible with automatic calculation of direction change

> in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed

2024-07-05



Technical parameters

Combi convection steam oven STEAMBOX electric 10x GN 1/1 touch screen automatic cleaning direct steam 400 V Model **SAP Code** 00011593 14. Exterior color of the device: 1. SAP Code: 00011593 Stainless steel 2. Net Width [mm]: 15. Adjustable feet: 860 Yes 3. Net Depth [mm]: 16. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented) 17. Stacking availability: 4. Net Height [mm]: 5. Net Weight [kg]: 18. Control type: 168.00 Digital 19. Additional information: 6. Gross Width [mm]: possibility of reverse door opening - handle on the right 955 side (must be specified when ordering) 7. Gross depth [mm]: 20. Steam type: Injection 8. Gross Height [mm]: 21. Chimney for moisture extraction: 1240 Yes 9. Gross Weight [kg]: 22. Delta T heat preparation: 178.00 10. Device type: 23. Automatic preheating: Electric unit 11. Power electric [kW]: 24. Automatic cooling: 15.700 25. Unified finishing of meals EasyService: 12. Loading: 400 V / 3N - 50 Hz

26. Night cooking:

No

13. Material:

AISI 304



Technical parameters



Combi convection steam oven STEAMBOX electric 10x GN 1/1 touch screen automatic cleaning direct steam 400 V **SAP Code** Model 00011593 27. Washing system: 40. Distance between the layers [mm]: Closed - efficient use of water and washing chemicals by repeated pumping 28. Detergent type: 41. Smoke-dry function: Liquid washing detergent + liquid rinse aid/vinegar or No washing tablets 29. Multi level cooking: 42. Interior lighting: 30. Advanced moisture adjustment: 43. Low temperature heat treatment: Supersteam - two steam saturation modes 31. Slow cooking: 44. Number of fans: from 50 °C 45. Number of fan speeds: 32. Fan stop: Immediate when the door is opened 33. Lighting type: 46. Number of programs: LED lighting in the doors, on both sides 34. Cavity material and shape: 47. USB port: AISI 304, with rounded corners for easy cleaning Yes, for uploading recipes and updating firmware 35. Reversible fan: 48. Door constitution: Vented safety double glass, removable for easy cleaning Yes 36. Sustaince box: 49. Number of preset programs: 37. Heating element material: 50. Number of recipe steps: Incoloy 38. Probe: 51. Minimum device temperature [°C]:

Optional

39. Shower: volitelná

50

300

52. Maximum device temperature [°C]:



Technical parameters

Combi convection steam oven STEAMBOX electric 10x GN 1/1 touch screen automatic cleaning direct steam 400 V			
Model	SAP Code	00011593	
53. Device heating type: Combination of steam and hot air		56. GN / EN size in device: GN 1/1	
54. HACCP: Yes		57. GN device depth: 65	
55. Number of GN / EN: 10		58. Food regeneration: Yes	