

Technical data sheet

Product features



Combi convection steam oven electric 5x GN 1/1 electromechanical, direct steam 400 V

Model	SAP Code	00011276
EPM 0511 E	A group of articles - web	Convection machines



- Steam type: Injection
- Number of GN / EN: 5
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Mechanical
- Humidity control: No
- Advanced moisture adjustment: No
- Delta T heat preparation: Yes
- Multi level cooking: No
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011276	Loading	400 V / 3N - 50 Hz
Net Width [mm]	870	Steam type	Injection
Net Depth [mm]	750	Number of GN / EN	5
Net Height [mm]	670	GN / EN size in device	GN 1/1
Net Weight [kg]	65.00	GN device depth	65
Power electric [kW]	6.300	Control type	Mechanical





Technical data sheet

Technical drawing



Combi convection steam oven electric 5x GN 1/1 electromechanical, direct steam 400 V

Model	SAP Code	00011276
EPM 0511 E	A group of articles - web	Convection machines



Technical data sheet



Product benefits

Combi convection steam oven electric 5x GN 1/1 electromechanical, direct steam 400 V

Model	SAP Code	00011276
EPM 0511 E	A group of articles - web	Convection machines

1

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

2

Manual controls

setting values using rotary knobs

3

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other
connects the connections, inlets, wastes and ventilation of the lower combi oven

4

Temperature range 30°C - 300°C

heating the chamber in the temperature range of 30 to 300 °C

5

Stainless steel construction

construction material is high quality stainless steel
ensuring long life
high hygiene standard

Technical data sheet

Technical parameters



Combi convection steam oven electric 5x GN 1/1 electromechanical, direct steam 400 V

Model	SAP Code	00011276
EPM 0511 E	A group of articles - web	Convection machines

1. SAP Code:

00011276

2. Net Width [mm]:

870

3. Net Depth [mm]:

750

4. Net Height [mm]:

670

5. Net Weight [kg]:

65.00

6. Gross Width [mm]:

810

7. Gross depth [mm]:

700

8. Gross Height [mm]:

780

9. Gross Weight [kg]:

75.00

10. Device type:

Electric unit

11. Power electric [kW]:

6.300

12. Loading:

400 V / 3N - 50 Hz

13. Material:

AISI 304

14. Exterior color of the device:

Stainless steel

15. Adjustable feet:

Yes

16. Humidity control:

No

17. Stacking availability:

Yes

18. Control type:

Mechanical

19. Steam type:

Injection

20. Sturdier version:

No

21. Chimney for moisture extraction:

Yes

22. Delta T heat preparation:

Yes

23. Cold smoke-dry function:

No

24. Unified finishing of meals EasyService:

No

25. Night cooking:

No

26. Multi level cooking:

No

27. Advanced moisture adjustment:

No

28. Slow cooking:

Ne

Technical data sheet

Technical parameters



Combi convection steam oven electric 5x GN 1/1 electromechanical, direct steam 400 V

Model	SAP Code	00011276
EPM 0511 E	A group of articles - web	Convection machines

29. Fan stop:

Interruption when door is opened, not braked

30. Lighting type:

LED lighting in the door, on one side

31. Cavity material and shape:

AISI 304, with rounded corners for easy cleaning

32. Reversible fan:

Yes

33. Sustaince box:

Yes

34. Heating element material:

Incoloy

35. Probe:

No

36. Shower:

No

37. Distance between the layers [mm]:

74

38. Smoke-dry function:

No

39. Interior lighting:

Yes

40. Low temperature heat treatment:

No

41. Number of fans:

1

42. Number of fan speeds:

2

43. USB port:

No

44. Door constitution:

Vented safety double glass, removable for easy cleaning

45. Minimum device temperature [°C]:

50

46. Maximum device temperature [°C]:

280

47. Device heating type:

Combination of steam and hot air

48. HACCP:

Yes

49. Number of GN / EN:

5

50. GN / EN size in device:

GN 1/1

51. GN device depth:

65

52. Food regeneration:

Yes

53. Cross-section of conductors CU [mm²]:

1

54. Diameter nominal:

DN 50

55. Water supply connection:

3/4"