



Blender motor 250 W variable speed

SAP Code Model 00013298



- Mixing speed [rpm]: 15000
- Whipping speed [rpm]: 2500 15000
- Material: ABS plastic
- Number of speeds of device: 9
- Control type: Digital
- Safety element: thermal overload protection
- Way of tool mounting: Bayonet coupling, double, sliding nut
- Engine protection: overheating protection
- Main switch: Yes
- Ergonomic handle: Yes
- Additional information: interchangeable whisking, mixing, homogenising and emulsifying attachments control board with SRS system for power and speed stabilisation

| SAP Code | 00013298 | Power electric [kW] | 0.250 |
|-----------------|----------|----------------------|--------------------|
| Net Width [mm] | 75 | Loading | 230 V / 1N - 50 Hz |
| Net Depth [mm] | 75 | Mixing speed [rpm] | 15000 |
| Net Height [mm] | 285 | Whipping speed [rpm] | 2500 - 15000 |
| Net Weight [kg] | 1.65 | | |

Technical data sheet





Blender motor 250 W variable speed

Model SAP Code 00013298

Engine only

option to choose accessories as needed

 cost savings no need to buy what I don't need or, on the other hand, additional machines

Compact design

conformity easy handling

- very easy to use for any operator in the kitchen

Variable speed

the possibility of processing different types of food

- multiple devices can be represented

Ergonomic handle

easy and convenient to use

- higher security
- less fatigue during use

SRS technology

easy and convenient to use

- perfect result even when mixing frozen foods

Bayonet clutch with star shape

perfect torque transmission resistance to breaking out

- perfect food processing
- durability

Technical data sheet



Technical parameters

| Blender motor 250 W variable | e speed | | |
|--------------------------------------|----------|--|--|
| Model | SAP Code | 00013298 | |
| | | | |
| 1. SAP Code: 00013298 | | 14. Number of speeds of device: | |
| 2. Net Width [mm]: 75 | | 15. Control type: Digital | |
| 3. Net Depth [mm]: 75 | | 16. Safety element: thermal overload protection | |
| 4. Net Height [mm]: 285 | | 17. Way of tool mounting: Bayonet coupling, double, sliding nut | |
| 5. Net Weight [kg]: 1.65 | | 18. Engine protection: overheating protection | |
| 6. Gross Width [mm]: 125 | | 19. Main switch: Yes | |
| 7. Gross depth [mm]: | | 20. Additional information: interchangeable whisking, mixing, homogenising and emulsifying attachments control board with SRS system for power and speed stabilisation | |
| 8. Gross Height [mm]: 400 | | 21. Ergonomic handle: Yes | |
| 9. Gross Weight [kg]: | | 22. Whipping speed [rpm]: 2500 - 15000 | |
| 0. Device type: Electric unit | | 23. Gasket: Yes | |
| 11. Material: ABS plastic | | 24. Connections material: Polymer | |
| 12. Power electric [kW]: 0.250 | | 25. Mixing speed [rpm]: 15000 | |

13. Loading:

230 V / 1N - 50 Hz