

Technical data sheet

Product features



Blast chiller/freezer 3x GN 1/1 digital control panel PET 230 V

Model	SAP Code	00012472
SHF 0311	A group of articles - web	Šokery a multifunkční zařízení



- Shock cooling cycle kg / min (+3 ° C): 9
- Shock freeze cycle kg / min (-18 ° C): 7
- Minimum device temperature [°C]: 3
- Maximum device temperature [°C]: -18
- Probe: 4-points
- Insulation thickness [mm]: 60
- Control type: Digital

SAP Code	00012472	Number of GN / EN	3
Net Width [mm]	650	GN / EN size in device	GN 1/1
Net Depth [mm]	600	GN device depth	40
Net Height [mm]	540	Shock cooling cycle kg / min (+3 ° C)	9
Net Weight [kg]	54.00	Shock freeze cycle kg / min (-18 ° C)	7
Power electric [kW]	0.510	Control type	Digital
Loading	230 V / 1N - 50 Hz		



Technical data sheet

Technical drawing



Blast chiller/freezer 3x GN 1/1 digital control panel PET 230 V

Model	SAP Code	00012472
SHF 0311	A group of articles - web	Šokery a multifunkční zařízení



Technical data sheet



Product benefits

Blast chiller/freezer 3x GN 1/1 digital control panel PET 230 V

Model	SAP Code	00012472
SHF 0311	A group of articles - web	Šokery a multifunkční zařízení

1

Very fast cooling and freezing

times faster cooling and freezing compared to a classic refrigerator/freezer

2

Controlled defrosting

safety and hygiene

3

Probe in standard equipment

accurate and safe cooling/freezing/defrosting thanks to core temperature measurement

4

Digital control

clarity and simplicity of operation

5

Autorepair surface

easy to maintain

Technical data sheet

Technical parameters



Blast chiller/freezer 3x GN 1/1 digital control panel PET 230 V

Model	SAP Code	00012472
SHF 0311	A group of articles - web	Šokery a multifunkční zařízení

1. SAP Code:

00012472

2. Net Width [mm]:

650

3. Net Depth [mm]:

600

4. Net Height [mm]:

540

5. Net Weight [kg]:

54.00

6. Gross Width [mm]:

695

7. Gross depth [mm]:

645

8. Gross Height [mm]:

675

9. Gross Weight [kg]:

62.10

10. Device type:

Electric unit

11. Opening of device:

Hinges on the left

12. Power electric [kW]:

0.510

13. Loading:

230 V / 1N - 50 Hz

14. Control type:

Digital

15. Refrigerant:

R452a

16. Number of GN / EN:

3

17. GN / EN size in device:

GN 1/1

18. GN device depth:

40

19. Minimum device temperature [°C]:

3

20. Maximum device temperature [°C]:

-18

21. Shock freeze cycle kg / min (-18 ° C):

7

22. Shock cooling cycle kg / min (+3 ° C):

9

23. Insulation thickness [mm]:

60

24. Probe:

4-points

25. Interior lighting:

No

26. HACCP:

No

27. Castors:

No

28. Cross-section of conductors CU [mm²]:

0,5