



| STEAMBOX electric convector 6x GN 1/1 boiler touch colored auto. washing |                           |                     |
|--|---------------------------|---------------------|
| Model  | SAP Code                  | 00038363            |
| STMB 0611 E  | A group of articles - web | Convection machines |




- Steam type: Symbiotic boiler and injection combination (patent)
- Number of GN / EN: 6
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Touchscreen
- Display size: 10"
- Humidity control: MeteoSystem regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Steamtuner 5-stage system of setting steam saturation by controlled combination of production by boiler or injection
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: Drawer program control of heat treatment for each dish separately
- Door constitution: Odvětrávané bezpečnostní trojité sklo, rozebiratelné pro snadné čištění


| SAP Code            | 00038363           | Steam type             | Symbiotic - boiler and injection combina-tion (patent) |
|---------------------|--------------------|------------------------|--|
| Net Width [mm]      | 860                | Number of GN / EN      | 6  |
| Net Depth [mm]      | 795                | GN / EN size in device | GN 1/1   |
| Net Height [mm]     | 835                | GN device depth        | 65   |
| Net Weight [kg]     | 107.00             | Control type           | Touchscreen  |
| Power electric [kW] | 11.400             | Display size           | 10"  |
| Loading             | 400 V / 3N - 50 Hz |                        |  |




Technical drawing

| STEAMBOX electric convector 6x GN 1/1 boiler touch colored auto. washing |                              |                     |
|--|------------------------------|---------------------|
| Model  | SAP Code                     | 00038363            |
| STMB 0611 E  | A group of<br>articles - web | Convection machines |











| STEAMBOX electric convector 6x GN 1/1 boiler touch colored auto. washing |            |                     |
|--|------------|---------------------|
| Model  | SAP Code   | 00038363            |
| STMB 0611 E  | A group of | Convection machines |

Triple glass door as standard

better thermal insulation, less frequent reheating, safer operation due to lower outer glass temperature, less radiant heat, less heat leakage, lower load on electronics and mechanical parts

Clear 10" touch screen corresponding to other RM line devices

simple intuitive operation using images and visualizations, the same intuitive operation as on other digital devices in the RM line

Smart cooking

Predefined basic programs for easy control with just a few touches

Symbiotic steam generation system

simultaneous use of "direct injection" and boiler, maintaining 100% humidity, or its regulation

\_\_\_ | Self-winding shower

vacuum probe

drum reel integrated in the combi oven body the shower is inaccessible after closing the door

Fan six-speed, reversible with automatic calculation of direction change

in cooperation with the symbiotic system, it ensures perfect distribution of steam without loss of its saturation, its operation is controlled by program or manually

External temperature probe
temperature probe placed outside the cooking space
option to choose from a single or multi-point probe or

Longitudinal drawers for GN

drawers placed at the "depth" of the machine option to replace with drawers for 600x400 trays

USB

downloading service reports upgrade software playback recipes

Automatic washing

integrated chamber washing system option to use liquid and tablet detergents option to use vinegar as a rinse aid the system also descales the micro-boiler

Meteo system

patented device for measuring steam saturation in real time and in steam mode, the only one on the market

Kit of two machines on top of each other

interconnection kit allowing two machines to be stacked on top of each other

interconnects connections, inlets, wastes and ventilation of the lower combi oven

Premix burner

the only burner with turbo pre-mixing of gas with air on the market

v"" burner design prevents backfire and banging this design saves 30% of gas compared to conventional burners"

Adjustment for roasting chicken

The combi oven chamber is designed to collect baked-on fat, the machine is equipped with a fat collection container



#### Technical parameters

| STEAMBOX electric convector 6          | x GN 1/1 boiler touch c   | colored auto. washing   |
|--|---------------------------|---|
| Model                                  | SAP Code                  | 00038363  |
| STMB 0611 E                            | A group of articles - web | Convection machines   |
| <b>1. SAP Code:</b> 00038363           |                           | <b>14. Exterior color of the device:</b> Stainless steel  |
| 2. Net Width [mm]: 860                 |                           | <b>15. Adjustable feet:</b> Yes   |
| <b>3. Net Depth [mm]:</b> 795          |                           | <b>16. Humidity control:</b> MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)             |
| 4. Net Height [mm]:<br>835             |                           | <b>17. Stacking availability:</b> Yes   |
| 5. Net Weight [kg]:<br>107.00          |                           | <b>18. Control type:</b> Touchscreen  |
| <b>6. Gross Width [mm]:</b> 955        |                           | <b>19. Additional information:</b> possibility of reverse door opening - handle on the right side (must be specified when ordering) |
| 7. Gross depth [mm]: 920               |                           | 20. Steam type: Symbiotic - boiler and injection combination (patent)   |
| 8. Gross Height [mm]:                  |                           | 21. Chimney for moisture extraction: Yes  |
| 9. Gross Weight [kg]:<br>128.00        |                           | 22. Delayed start: Yes  |
| 10. Device type:<br>Electric unit      |                           | 23. Display size:   |
| 11. Power electric [kW]: 11.400        |                           | 24. Delta T heat preparation: Yes   |
| <b>12. Loading:</b> 400 V / 3N - 50 Hz |                           | 25. Automatic preheating: Yes   |
| 13. Material:                          |                           | 26. Automatic cooling:  |

Yes

AISI 304



#### Technical parameters

| STEAMBOX electric convector 6x 0  | 6N 1/1 boiler touch colo  | red auto. washing                               |
|---|---------------------------|---|
| Model   | SAP Code                  | 00038363  |
| STMB 0611 E   | A group of articles - web | Convection machines                             |
| <b>27. Cold smoke-dry function:</b> Yes   |                           | <b>39. Sustaince box:</b> Yes                   |
| 28. Unified finishing of meals EasyService: Yes   |                           | <b>40. Heating element material:</b> Incoloy    |
| 29. Night cooking: Yes  |                           | <b>41. Probe:</b> Yes                           |
| 30. Washing system: Closed - efficient use of water and washing chemicals by repeated pumping   |                           | <b>42. Shower:</b> Hand winder                  |
| 31. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets  |                           | <b>43. Distance between the layers [mm]:</b> 70 |
| 32. Multi level cooking:  Drawer program - control of heat treatment for each dish separately   |                           | <b>44. Smoke-dry function:</b> Yes              |
| <b>33. Advanced moisture adjustment:</b> Steamtuner - 5-stage system of setting steam saturation by controlled combination of production by boiler or injection |                           | <b>45. Interior lighting:</b> Yes               |
| <b>34. Slow cooking:</b> from 30 °C - the possibility of rising   |                           | <b>46. Low temperature heat treatment:</b> Yes  |
| 35. Fan stop: Immediate when the door is opened   |                           | <b>47. Number of fans:</b>                      |
| <b>36. Lighting type:</b> LED lighting in the doors, on both sides  |                           | <b>48. Number of fan speeds:</b>                |
| <b>37. Cavity material and shape:</b> AISI 304, with rounded corners for easy cleaning  |                           | <b>49. Number of programs:</b> 1000             |

38. Reversible fan:

Yes

50. USB port:

Yes, for uploading recipes and updating firmware



#### Technical parameters

| STEAMBOX electric convector 6x GN 1/1 boiler touch colored auto. washing                              |                           |  |
|---|---------------------------|--|
| Model   | SAP Code                  | 00038363   |
| STMB 0611 E   | A group of articles - web | Convection machines                                    |
| <b>51. Door constitution:</b> Odvětrávané bezpečnostní trojité sklo, rozebiratelné pro snadné čištění |                           | <b>58. Number of GN / EN:</b>                          |
| <b>52. Number of preset programs:</b> 100   |                           | <b>59. GN / EN size in device:</b> GN 1/1              |
| 53. Number of recipe steps:   |                           | <b>60. GN device depth:</b> 65                         |
| <b>54. Minimum device temperature [°C]:</b> 30  |                           | <b>61. Food regeneration:</b> Yes                      |
| <b>55. Maximum device temperature [°C]:</b> 300   |                           | 62. Cross-section of conductors CU [mm <sup>2</sup> ]: |
| <b>56. Device heating type:</b> Combination of steam and hot air                                      |                           | <b>63. Diameter nominal:</b> DN 50                     |
| 57. HACCP:  |                           | 64. Water supply connection:                           |

3/4"

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

Yes