

Technical data sheet

Product features



Cooling tabletop electric GN1/1, 1 door, 2x 1/2 drawers, with rim, unit on the left, stainless steel 230V OOP

Model	SAP Code	00018516
-------	----------	----------



- Material: Stainless steel
- GN / EN size in device: GN 1/1
- Number of GN / EN: 3
- Number of doors: 1
- Number of drawers: 2
- Control type: Digital
- Minimum device temperature [°C]: -2
- Maximum device temperature [°C]: 8
- Max ambient temperature [°C]: 43
- Insulation thickness [mm]: 70
- Unit: Left

SAP Code	00018516	Number of doors	1
Net Width [mm]	1880	Number of drawers	2
Net Depth [mm]	700	Number of GN / EN	3
Net Height [mm]	850	GN / EN size in device	GN 1/1
Net Weight [kg]	140.00	Minimum device temperature [°C]	-2
Power electric [kW]	0.380	Maximum device temperature [°C]	8
Loading	230 V / 1N - 50 Hz	Refrigerant	R290

Technical data sheet

Technical parameters



Cooling tabletop electric GN1/1, 1 door, 2x 1/2 drawers, with rim, unit on the left, stainless steel 230V OOP

Model

SAP Code

00018516

1. SAP Code:

00018516

2. Net Width [mm]:

1880

3. Net Depth [mm]:

700

4. Net Height [mm]:

850

5. Net Weight [kg]:

140.00

6. Gross Width [mm]:

1950

7. Gross depth [mm]:

750

8. Gross Height [mm]:

900

9. Gross Weight [kg]:

160.00

10. Device type:

Electric unit

11. Power electric [kW]:

0.380

12. Loading:

230 V / 1N - 50 Hz

13. Refrigerant:

R290

14. Material:

Stainless steel

15. Max ambient temperature [°C]:

43

16. Device properties 2:

Cooling

17. GN / EN size in device:

GN 1/1

18. Number of GN / EN:

3

19. Adjustable feet:

Yes

20. Pizza design:

No

21. Insulation thickness [mm]:

70

22. Number of doors:

1

23. Number of drawers:

2

24. Unit:

Left

25. Control type:

Digital

26. Minimum device temperature [°C]:

-2

27. Maximum device temperature [°C]:

8

28. Gross Volume [m3]:

1.316

Technical data sheet

Technical parameters



Cooling tabletop electric GN1/1, 1 door, 2x 1/2 drawers, with rim, unit on the left, stainless steel 230V OOP

Model

SAP Code

00018516

29. Net Volume [m3]:

1.119

30. Cross-section of conductors CU [mm²]:

0,5

– Výkon (kW): 2,4-3,3 (230 V)