

Technical data sheet



Product features

Fry-top griddle plate 71x65 electric combined on open cabinet 400 V

Model	SAP Code	00012403
--------------	-----------------	----------



- Top type: Combined
- Worktop material: Sandblasted steel
- Maximum device temperature [°C]: 300

SAP Code	00012403	Net Weight [kg]	126.00
Net Width [mm]	800	Power electric [kW]	12.000
Net Depth [mm]	900	Loading	400 V / 3N - 50 Hz
Net Height [mm]	900	Top type	Combined

Technical data sheet



Product benefits

Fry-top griddle plate 71x65 electric combined on open cabinet 400 V

Model

SAP Code

00012403

1

All-stainless design

long life
corrosion resistance of the top plate material

- savings on service interventions
- higher corrosion resistance

2

Degree of protection of the control elements IPX4

maintenance-free system
resistance to splash water
long life

- savings on service interventions
- easy cleaning and maintenance of equipment

3

Outlet for waste liquids

ensures that oil drips into the socket

- easy maintenance
- easy cleaning

4

High detachable hem

better hygienic conditions
preventing grease from splashing onto ancillary equipment

- easy maintenance
- easy cleaning

5

Combined steel plate

good heat transfer and the surface does not get scratched
enables preparation on smooth or grooved plates

- time-saving in food preparation
- easy preparation of different types of dishes

6

Two-zone hotplate control

allows you to prepare several dishes at the same time in different stages of preparation

- time saving
- high productivity

Technical data sheet



Technical parameters

Fry-top griddle plate 71x65 electric combined on open cabinet 400 V

Model	SAP Code	00012403
--------------	-----------------	----------

1. SAP Code:

00012403

2. Net Width [mm]:

800

3. Net Depth [mm]:

900

4. Net Height [mm]:

900

5. Net Weight [kg]:

126.00

6. Gross Width [mm]:

970

7. Gross depth [mm]:

840

8. Gross Height [mm]:

1160

9. Gross Weight [kg]:

145.00

10. Device type:

Electric unit

11. Construction type of device:

Stationary

12. Power electric [kW]:

12.000

13. Loading:

400 V / 3N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 304 top plate, AISI 430 cladding

16. Worktop material:

Sandblasted steel

17. Worktop Thickness [mm]:

15.00

18. Maximum device temperature [°C]:

300

19. Minimum device temperature [°C]:

50

20. Adjustable feet:

Yes

21. Top type:

Combinated

22. Cross-section of conductors CU [mm²]:

4

- Výkon (kW): 30-37 (230 V); 53-64 (400 V)