

Technical data sheet

Product features



Steak grill electric double 65x48 table durable chrome

Model	SAP Code	00021115
KD 66 E	A group of articles - web	Grills and grill plates



- Top type: Smooth
- Griddle dimensions [mm x mm]: 650 x 480 + 320 x 380 + 320 x 380
- Griddle thickness [mm]: 10.00
- Worktop material: AISI 304
- Container for liquid fat: Yes
- Independent heating zones: Separate control for each heating zone on the bottom plate and for the top plates
- Maximum device temperature [°C]: 300
- Surface finish: durable chrome

SAP Code	00021115	Power electric [kW]	12.000
Net Width [mm]	710	Loading	2x 230 V / 1N - 50 Hz + 400 V / 3N - 50 Hz
Net Depth [mm]	725	Griddle dimensions [mm x mm]	650 x 480 + 320 x 380 + 320 x 380
Net Height [mm]	540	Top type	Smooth
Net Weight [kg]	60.00		

Technical data sheet



Product benefits

Steak grill electric double 65x48 table durable chrome

Model	SAP Code	00021115
KD 66 E	A group of articles - web	Grills and grill plates

1

Nationheres

Only stainless steel used for food contact

2

Chrome 0.03mm

non -stick dishes when roasting easier to clean the board

3

Self -controlled control for upper and lower heating

can i control both areas independent of each other

4

Upper contact area with Teflon canvas

non -backed rollers
uniform warming the rolls

Technical data sheet



Technical parameters

Steak grill electric double 65x48 table durable chrome

Model	SAP Code	00021115
KD 66 E	A group of articles - web	Grills and grill plates

1. SAP Code:

00021115

2. Net Width [mm]:

710

3. Net Depth [mm]:

725

4. Net Height [mm]:

540

5. Net Weight [kg]:

60.00

6. Gross Width [mm]:

725

7. Gross depth [mm]:

710

8. Gross Height [mm]:

540

9. Gross Weight [kg]:

65.00

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Power electric [kW]:

12.000

13. Loading:

2x 230 V / 1N - 50 Hz + 400 V / 3N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 430

16. Indicators:

operation and warm-up

17. Worktop material:

AISI 304

18. Surface finish:

durable chrome

19. Maximum device temperature [°C]:

300

20. Minimum device temperature [°C]:

50

21. Griddle dimensions [mm x mm]:

650 x 480 + 320 x 380 + 320 x 380

22. Griddle thickness [mm]:

10.00

23. Container for liquid fat:

Yes

24. Independent heating zones:

Separate control for each heating zone on the bottom plate and for the top plates

25. Uniform heating:

Yes

26. Top type:

Smooth

27. Cross-section of conductors CU [mm²]:

10