

### Product features

Toaster 6x holders 2x grid		
Model	SAP Code	00004296




- Standard equipment for device: 6x tongs, 2x grid
- Timer: Yes
- Material: Stainless steel
- Indicators: operation and warm-up
- Removable rear wall of the device: Yes
- Container for liquid fat: Yes


SAP Code	00004296	Net Weight [kg]	11.00
Net Width [mm]	453	Power electric [kW]	3.000
Net Depth [mm]	274	Loading	230 V / 1N - 50 Hz
Net Height [mm]	403	Standard equipment for device	6x tongs, 2x grid




Technical drawing

Toaster 6x holders 2x grid		
Model	SAP Code	00004296









#### **Product benefits**

Toaster 6x holders 2x grid		
Model	SAP Code	00004296

#### All-stainless design

only stainless steel intended for food contact is used

- absolutely rust-proof and non-magnetic design resists even weak acids easier compliance with hygiene standards (HACCP); easy maintenance and cleaning
- Run and warm-up light

optical possibility to check the status of the device

- the operator immediately knows what state the appliance is in on/off, heating/not heating
- Separate control for individual sections the possibility of a heating system separately
  - greater variability of use
- Catch container for breadcrumbs breadcrumbs fall outside the furnace
  - no crumbs falling off
- Removable back wall

  possibility to open the back wall of the device

  possible filling of the equipment by the operator
- Silicon heaters
  immediate onset of heat
  intense radiant heat
  - the device can be switched off even during the operating day
  - toasted food vigorously and without overheating inside
  - faster food preparation

## The tongs and grid are part of the standard equipment

I can put the food on the grate or put it in tongs

- universally applicable equipment
- I can prepare different types of food using standard equipment



### Technical parameters

Toaster 6x holders 2x grid		
Model	SAP Code	00004296
<b>1. SAP Code:</b> 00004296		12. Material: Stainless steel
<b>2. Net Width [mm]:</b> 453		13. Power electric [kW]: 3.000
3. Net Depth [mm]: 274		<b>14. Loading:</b> 230 V / 1N - 50 Hz
4. Net Height [mm]:		<b>15. Standard equipment for device:</b> 6x tongs, 2x grid
5. Net Weight [kg]: 11.00		16. Protection of controls:
6. Gross Width [mm]: 355		17. Timer: Yes
<b>7. Gross depth [mm]:</b> 500		18. Removable rear wall of the device:  Yes
8. Gross Height [mm]: 440		19. Container for liquid fat:  Yes
9. Gross Weight [kg]: 12.00		20. Indicators: operation and warm-up
10. Device type:  Electric unit		21. Cross-section of conductors CU [mm²]: 0,75

11. Construction type of device:

Table top