

Technical data sheet



Product features

Clam grill electric 32x48 counter top

Model	SAP Code	00001658
--------------	-----------------	----------



- Griddle dimensions [mm x mm]: 320 x 480 + 320 x 380
- Griddle thickness [mm]: 10.00
- Container for liquid fat: Yes
- Independent heating zones: Separate control for top and bottom plate
- Maximum device temperature [°C]: 300
- Surface finish: polished chrome 0.03 mm

SAP Code	00001658	Net Weight [kg]	40.00
Net Width [mm]	328	Power electric [kW]	6.000
Net Depth [mm]	654	Loading	230 V / 1N - 50 Hz
Net Height [mm]	406	Griddle dimensions [mm x mm]	320 x 480 + 320 x 380

Clam grill electric 32x48 counter top

Model

SAP Code

00001658

1

All-stainless design

only stainless steel intended for food contact is used

- absolutely rust-proof and non-magnetic design
- resists even weak acids easier compliance with hygiene standards (HACCP); easy maintenance and cleaning

2

Surface treatment of the grill plate chrome 0.03mm

non-stickiness of food when frying, easier cleaning of the plate

- faster and easier work for the operator higher food quality

3

Separate control for upper and lower heating

I can control both surfaces independently

- better controllability and energy saving more even cooking of food I can prepare more types of food and faster on one device

4

Upper contact surface with Teflon cloth

no-bake rolls
uniform heating of the roll

- faster and easier work for the operator
- faster preparation
- preserving the shape of the food
- quicker searing of the surface of the food on both sides juicier meat

Technical data sheet



Technical parameters

Clam grill electric 32x48 counter top

Model

SAP Code

00001658

1. SAP Code:

00001658

2. Net Width [mm]:

328

3. Net Depth [mm]:

654

4. Net Height [mm]:

406

5. Net Weight [kg]:

40.00

6. Gross Width [mm]:

395

7. Gross depth [mm]:

705

8. Gross Height [mm]:

482

9. Gross Weight [kg]:

44.00

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Power electric [kW]:

6.000

13. Loading:

230 V / 1N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 430

16. Indicators:

operation and warm-up

17. Surface finish:

polished chrome 0.03 mm

18. Maximum device temperature [°C]:

300

19. Minimum device temperature [°C]:

50

20. Griddle dimensions [mm x mm]:

320 x 480 + 320 x 380

21. Griddle thickness [mm]:

10.00

22. Container for liquid fat:

Yes

23. Independent heating zones:

Separate control for top and bottom plate

24. Uniform heating:

Yes

25. Cross-section of conductors CU [mm²]:

2,5

- Výkon (kW): 11-17 (230 V); 19-30 (400 V)