

Technical data sheet

Product features



Fry Top Griddle 65x48 electric durable chrome smooth without cabinet 400 V

Model	SAP Code	00020985
FTHC 60 EL	A group of articles - web	Grills and grill plates



- Top type: Smooth
- Griddle dimensions [mm x mm]: 650 x 480
- Griddle thickness [mm]: 10.00
- Container for liquid fat: Yes
- Independent heating zones: Separate control for each heating zone
- Maximum device temperature [°C]: 300
- Surface finish: polished chrome 0.03 mm
- Removable rim: No

SAP Code	00020985	Power electric [kW]	6.000
Net Width [mm]	658	Loading	400 V / 3N - 50 Hz
Net Depth [mm]	609	Griddle dimensions [mm x mm]	650 x 480
Net Height [mm]	290	Top type	Smooth
Net Weight [kg]	45.00		

Technical data sheet



Product benefits

Fry Top Griddle 65x48 electric durable chrome smooth without cabinet 400 V

Model	SAP Code	00020985
FTHC 60 EL	A group of articles - web	Grills and grill plates

1

Nationheres

long life
stainless steel resistance of AISI 304
the material does not rue

2

Degree of protection of controls IPX4

maintenance -free
water resistance
long life

3

Waste fluid socket

ensures oil dripping into a socket

4

Tall non -removable hem

Better Hygienic Conditions
Preventing fat spraying on a secondary device

5

A smooth horn made of chrome steel

The product is less baked and cleaned better
good warming of meat with groove

6

A kernel for use on a table or on a bedding

variable use
Possibility to place in smaller spaces

Technical data sheet

Technical parameters



Fry Top Griddle 65x48 electric durable chrome smooth without cabinet 400 V

Model	SAP Code	00020985
FTHC 60 EL	A group of articles - web	Grills and grill plates

1. SAP Code:

00020985

2. Net Width [mm]:

658

3. Net Depth [mm]:

609

4. Net Height [mm]:

290

5. Net Weight [kg]:

45.00

6. Gross Width [mm]:

725

7. Gross depth [mm]:

710

8. Gross Height [mm]:

540

9. Gross Weight [kg]:

50.00

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Power electric [kW]:

6.000

13. Loading:

400 V / 3N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 430

16. Indicators:

operation and warm-up

17. Surface finish:

polished chrome 0.03 mm

18. Maximum device temperature [°C]:

300

19. Minimum device temperature [°C]:

50

20. Adjustable feet:

Yes

21. Griddle dimensions [mm x mm]:

650 x 480

22. Griddle thickness [mm]:

10.00

23. Container for liquid fat:

Yes

24. Independent heating zones:

Separate control for each heating zone

25. Removable rim:

No

26. Uniform heating:

Yes

27. Top type:

Smooth

28. Cross-section of conductors CU [mm²]:

1