

Technical data sheet

Product features



Fry Top Griddle 32x48 electric durable chrome grooved table 230 v

Model	SAP Code	00020933
FTRC 30 E	A group of articles - web	Grills and grill plates



- Top type: Grooved
- Griddle dimensions [mm x mm]: 320 x 480
- Griddle thickness [mm]: 10.00
- Container for liquid fat: Yes
- Maximum device temperature [°C]: 300
- Surface finish: durable chrome
- Removable rim: No

SAP Code	00020933	Power electric [kW]	3.000
Net Width [mm]	328	Loading	230 V / 1N - 50 Hz
Net Depth [mm]	541	Griddle dimensions [mm x mm]	320 x 480
Net Height [mm]	285	Top type	Grooved
Net Weight [kg]	21.00		


Technical data sheet

Technical drawing



Fry Top Griddle 32x48 electric durable chrome grooved table 230 v

Model	SAP Code	00020933
FTRC 30 E	A group of articles - web	Grills and grill plates



Technical data sheet

Product benefits



Fry Top Griddle 32x48 electric durable chrome grooved table 230 v

Model	SAP Code	00020933
FTRC 30 E	A group of articles - web	Grills and grill plates

1

Nationheres

long life
stainless steel resistance of AISI 304
the material does not rue

2

Degree of protection of controls IPX4

maintenance -free
water resistance
long life

3

Waste fluid socket

ensures oil dripping into a socket

4

Tall non -removable hem

Better Hygienic Conditions
Preventing fat spraying on a secondary device

5

Combined plate made of chrome steel

The product is less baked and cleaned better
good warming of meat with groove

6

A kernel for use on a table or on a bedding

variable use
Possibility to place in smaller spaces

Technical data sheet

Technical parameters



Fry Top Griddle 32x48 electric durable chrome grooved table 230 v

Model	SAP Code	00020933
FTRC 30 E	A group of articles - web	Grills and grill plates

1. SAP Code:

00020933

2. Net Width [mm]:

328

3. Net Depth [mm]:

541

4. Net Height [mm]:

285

5. Net Weight [kg]:

21.00

6. Gross Width [mm]:

670

7. Gross depth [mm]:

395

8. Gross Height [mm]:

362

9. Gross Weight [kg]:

22.00

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Power electric [kW]:

3.000

13. Loading:

230 V / 1N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 430

16. Indicators:

operation and warm-up

17. Surface finish:

durable chrome

18. Maximum device temperature [°C]:

300

19. Minimum device temperature [°C]:

50

20. Adjustable feet:

Yes

21. Griddle dimensions [mm x mm]:

320 x 480

22. Griddle thickness [mm]:

10.00

23. Container for liquid fat:

Yes

24. Removable rim:

No

25. Uniform heating:

Yes

26. Top type:

Grooved

27. Cross-section of conductors CU [mm²]:

0,75