

# Technical data sheet

Product features



## STEAMBOX gas convection oven 20x GN 1/1 touch digital boiler

<b>Model</b>	<b>SAP Code</b>	00008612
SDBB 2011 G	<b>A group of articles - web</b>	Convection machines

- Steam type: Symbiotic - boiler and injection combination (patent)
- Number of GN / EN: 20
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Digital
- Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Supersteam - two steam saturation modes
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: No
- Door constitution: Vented safety double glass, removable for easy cleaning

<b>SAP Code</b>	00008612	<b>Power gas [kW]</b>	38.000
<b>Net Width [mm]</b>	995	<b>Type of gas</b>	Natural Gas
<b>Net Depth [mm]</b>	835	<b>Steam type</b>	Symbiotic - boiler and injection combination (patent)
<b>Net Height [mm]</b>	1850	<b>Number of GN / EN</b>	20
<b>Net Weight [kg]</b>	300.00	<b>GN / EN size in device</b>	GN 1/1
<b>Power electric [kW]</b>	3.300	<b>GN device depth</b>	65
<b>Loading</b>	230 V / 1N - 50 Hz	<b>Control type</b>	Digital

# Technical data sheet

## Product benefits



### STEAMBOX gas convection oven 20x GN 1/1 touch digital boiler

<b>Model</b>	<b>SAP Code</b>	00008612
SDBB 2011 G	<b>A group of articles - web</b>	Convection machines

- 1 A symbiotic steam generation system**  
simultaneous use of direct injection and boiler, maintenance of 100% humidity, or its regulation
- 2 Digital display**  
simple multi-line backlit display of 99 programs with 9 cooking phases
- 3 Weather system**  
patented device for measuring steam saturation in real time and in steam mode, the only one on the market
- 4 Steam tuner**  
a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process
- 5 Pass-through door**  
the door is also built into the back of the combi oven, while full control is retained from the side of the cook enables the distribution of the delivery area and the kitchen
- 6 Adaptation for roasting chickens**  
the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat
- 7 A kit of two machines on top of each other**  
connection kit allowing two machines to be placed on top of each other  
connects the connections, inlets, wastes and ventilation of the lower combi oven
- 8 Premix burner**  
the only burner with a turbo pre-mixing gas with air on the market  
the structure of the burner to V which prevents backfill and banging  
This design saves 30 % of gas compared to conventional burners
- 9 Automatic washing**  
integrated chamber washing system  
possibility to use liquid and tablet detergents  
option to use vinegar as a rinse agent  
the system simultaneously descales the micro-boiler
- 10 Self-supporting shower**  
drum winch integrated in the body of the kettle  
the shower is inaccessible when the door is closed
- 11 Six-speed fan, reversible with automatic calculation of direction change**  
in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness  
its operation is controlled by the program or manually
- 12 External temperature probe**  
temperature probe located outside the cooking area  
choice of single or multipoint probe or vacuum probe
- 13 Longitudinal insertion to GN**  
penetration placed on the "depth" of the machine  
exchangeable for 600x400 sheet metal inserts
- 14 USB**  
downloading service reports  
software upgrade  
recipe playback

# Technical data sheet

Technical parameters



## STEAMBOX gas convection oven 20x GN 1/1 touch digital boiler

<b>Model</b>	<b>SAP Code</b>	00008612
SDBB 2011 G	<b>A group of articles - web</b>	Convection machines

**1. SAP Code:**

00008612

**2. Net Width [mm]:**

995

**3. Net Depth [mm]:**

835

**4. Net Height [mm]:**

1850

**5. Net Weight [kg]:**

300.00

**6. Gross Width [mm]:**

1150

**7. Gross depth [mm]:**

1050

**8. Gross Height [mm]:**

2100

**9. Gross Weight [kg]:**

310.00

**10. Device type:**

Combined unit

**11. Power electric [kW]:**

3.300

**12. Loading:**

230 V / 1N - 50 Hz

**13. Power gas [kW]:**

38.000

**14. Type of gas:**

Natural Gas

**15. Material:**

AISI 304

**16. Exterior color of the device:**

Stainless steel

**17. Adjustable feet:**

Yes

**18. Humidity control:**

MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)

**19. Stacking availability:**

No

**20. Control type:**

Digital

**21. Additional information:**

possibility of reverse door opening - handle on the right side (must be specified when ordering)

**22. Steam type:**

Symbiotic - boiler and injection combination (patent)

**23. Chimney for moisture extraction:**

Yes

**24. Delta T heat preparation:**

Yes

**25. Automatic preheating:**

Yes

**26. Automatic cooling:**

Yes

# Technical data sheet

Technical parameters



## STEAMBOX gas convection oven 20x GN 1/1 touch digital boiler

<b>Model</b>	<b>SAP Code</b>	00008612
SDBB 2011 G	<b>A group of articles - web</b>	Convection machines

### 27. Unified finishing of meals EasyService:

No

### 28. Night cooking:

No

### 29. Multi level cooking:

No

### 30. Advanced moisture adjustment:

Supersteam - two steam saturation modes

### 31. Slow cooking:

from 30 °C - the possibility of rising

### 32. Fan stop:

Immediate when the door is opened

### 33. Lighting type:

LED lighting in the doors, on both sides

### 34. Cavity material and shape:

AISI 304, with rounded corners for easy cleaning

### 35. Reversible fan:

Yes

### 36. Sustance box:

Yes

### 37. Probe:

Yes

### 38. Shower:

Hand winder

### 39. Distance between the layers [mm]:

70

### 40. Smoke-dry function:

No

### 41. Interior lighting:

Yes

### 42. Low temperature heat treatment:

Yes

### 43. Number of fans:

2

### 44. Number of fan speeds:

6

### 45. Number of programs:

99

### 46. USB port:

Yes, for uploading recipes and updating firmware

### 47. Door constitution:

Vented safety double glass, removable for easy cleaning

### 48. Number of preset programs:

40

### 49. Number of recipe steps:

9

### 50. Minimum device temperature [°C]:

30

### 51. Maximum device temperature [°C]:

300

### 52. Device heating type:

Combination of steam and hot air

### 53. HACCP:

Yes

### 54. Number of GN / EN:

20

# Technical data sheet

Technical parameters



## STEAMBOX gas convection oven 20x GN 1/1 touch digital boiler

<b>Model</b>	<b>SAP Code</b>	00008612
SDBB 2011 G	<b>A group of articles - web</b>	Convection machines

**55. GN / EN size in device:**

GN 1/1

---

**59. Cross-section of conductors CU [mm<sup>2</sup>]:**

0,75

---

**56. GN device depth:**

65

---

**60. Diameter nominal:**

DN 50

---

**57. Food regeneration:**

Yes

---

**61. Water supply connection:**

3/4"

---

**58. Connection to a ball valve:**

1/2